


Timers for all Applications



Fuji multi-mode timers with full features

Ease of use: As the time range is adjusted, the corresponding display changes.

Full functionality: Up to four output modes can be selected simply with the turn of a screw. All outputs contain 5A, DPDT relays.

LED indicators

Miniature DIN timers are small and accurate

Small size: Under one inch wide

Easy operation: A simple dial allows easy setup for the operator.

Accuracy: The timer will perform its timing function with repeatable accuracy of +/- 1% of the setting.



Koyo digital timers: powerful but easy to use

This full-function timer has all the bells and whistles, including full programmability:

Timing ranges and modes: Seconds to hours time ranges with decimal selection and up and down timing modes accommodate a wide range of applications.

Output modes: Five output modes, from on-delay to one-shot, use a reliable 2A relay to operate the controlled device.

Tamper-proof: Key protection can be set for individual keys to prevent unintentional changes by the operator.



ST7P Series	MS4S Series	KT-V4S Series
--------------------	--------------------	----------------------



Display	Manual dial Time setting Output LED indicator	Manual dial Time setting Power LED indicator Output LED indicator Output mode setting	4-digit green LED display for time setting 4-Digit red LED display for current time Output LED indicator Programming indicators
Input Power	100-120 VAC or 24 VDC	100-240 VAC or 24 VDC/AC	85-260 VAC or 10-26 VDC
Inputs	Timed signal	Reset signal Start signal Gate signal Timed signal	Start signal Reset signal Timed signal
Outputs	Normally-open DPDT Normally-closed DPDT	Normally-open DPDT Normally-closed DPDT	1 SPDT DC NPN transistor
Contact Rating	3 A @ 240 VAC (resistive load)	5 A @ 250 VAC (resistive load)	Mechanical: 2 A @ 220 VAC Transistor: 100 mA @ 24 VDC
Output Modes	On-delay	On-delay Flicker One shot Off-delay	On-delay Flicker One shot Off-delay Accumulation
Time Ranges	0.4 seconds to 60 minutes	0.05 seconds to 60 hours	0.001 seconds to 999.9 hours
Enclosure Rating	NEMA 1	NEMA 1	IP65 - faceplate
Agency Approvals	UL/CSA/CE/TUV	UL/CSA/CE/TUV	UL/CSA/CE
Price	starting at \$38.75	starting at \$48.00	starting at \$100.00

Fuji 1/16 DIN Super Timers

Overview

The MS4S series super timers are 1/16 DIN style timing relays designed for process control, machine tool control, safety control and many other types of applications. The timers are plug-in 8-pin or 11-pin surface/DIN-rail mountable with up to four selectable modes of operation and four selectable timing ranges.



Features

MS4SM Series

- Multi-mode timer with mode indication. On-delay (PO), flicker (FL), one-shot (OS), or signal off-delay (SF)
- 11-pin plug-in with start, reset and gate (interrupt) input signals and a DPDT contact output
- Timing range from 0.05 seconds to 60 hours
- Timer scale with selectable ranges of 0-6, 0-12, 0-30 and 0-60
- Timing units in selectable ranges of 0.1s, sec, min and hrs
- Power on LED indicator (green) flickers during timing operation, UP (red) LED is on when normally open contact is closed

MS4SA Series

- On-delay timer
- 8-pin plug-in with a DPDT contact output
- Timing range from 0.05 seconds to 60 hours

- Timer scale with selectable ranges of 0-6, 0-12, 0-30 and 0-60
- Timing units in selectable ranges of 0.1s, sec, min and hrs
- Power on LED indicator (green) flickers during timing operation, UP (red) LED is on when normally open contact is closed

MS4SC Series


- On-delay timer
- 8-pin plug-in with a SPDT timed contact output and a SPDT instantaneous contact output
- Timing range from 0.05 seconds to 60 hours
- Timer scale with selectable ranges of 0-6, 0-12, 0-30 and 0-60
- Timing units in selectable ranges of 0.1s, sec, min and hrs
- Power on LED indicator (green) flickers during timing operation, UP (red) LED is on when normally open contact is closed

Product Selection Guide

Part Number	Description	Voltage	Time Range	Price
MS4SM-AP-ADC	Multi-mode timer with selectable timing range from 0.05s to 60 hours. Input power is 100 - 240 VAC. DPDT relay output. 11-pin connection. UL, CSA, TÜV approved. <i>Note:</i> Socket mounts must be purchased separately	100-240 VAC	0.05 seconds to 60 hours	\$52.00
MS4SA-AP-ADC	On-delay timer with selectable timing range from 0.05s to 60 hours. Input power is 100 - 240 VAC. DPDT relay output. 8-pin connection. UL, CSA, TÜV approved. <i>Note:</i> Socket mounts must be purchased separately		0.05 seconds to 60 hours	\$52.00
MS4SC-AP-ADC	On-delay timer with selectable timing range from 0.05s to 60 hours. Input power is 100 - 240 VAC. SPDT timed relay output and SPDT instantaneous relay output. 8-pin connection. UL, CSA, TÜV approved		0.05 seconds to 60 hours	\$52.00
MS4SM-CE-ADC	Multi-mode timer with selectable timing range from 0.05s to 60 hours. Input power is 24 VDC/AC DPDT relay output. 11-pin connection. UL, CSA, TÜV approved. <i>Note:</i> Socket mounts must be purchased separately	24 VDC/AC	0.05 seconds to 60 hours	\$52.00
MS4SA-CE-ADC	On-delay timer with selectable timing range from 0.05s to 60 hours. Input power is 24 VDC/AC. DPDT relay output. 8-pin connection. UL, CSA, TÜV approved. <i>Note:</i> Socket mounts must be purchased separately		0.05 seconds to 60 hours	\$52.00
MS4SC-CE-ADC	On-delay timer with selectable timing range from 0.05s to 60 hours. Input power is 24 VDC/AC. SPDT timed relay output and SPDT instantaneous relay output. 8-pin connection. UL, CSA, TÜV approved. <i>Note:</i> Socket mounts must be purchased separately		0.05 seconds to 60 hours	\$48.00
TP411X	DIN rail/surface mount socket for MS4SM series timers. UL, CSA, TÜV approved	N/A	N/A	\$7.25
TP411SBA	Panel mount socket for MS4SM series timers. UL, CSA, TÜV approved, requires PANEL-16*			\$7.25
TP48X	DIN rail/surface mount socket for MS4SA and MS4SC series timers. UL, CSA, TÜV approved			\$7.25
TP48SB	Panel mount socket for MS4SA and MS4SC series timers. UL, CSA, TÜV approved, requires PANEL-16*			\$7.25
PANEL-16	Mounting clip for 1/16th DIN timers and temperature/process controllers, for door (flush) mounting. 5 clips per package			\$12.00


*Panel clips for mounting through a door are optional and must be purchased separately.

Control



Dimensions (timer and socket assembly)

mm [inches]



Fuji Miniature DIN Super Timers



Overview


The ST7P is a compact and highly accurate timer. It is an on-delay operation type with a single timing range. These timers are designed to optimize mounting space in small areas. Mounting is by DIN rail or by securing directly to a panel with a fastener.

Features


- Highly accurate, with a repeat accuracy within $\pm 1\%$ at maximum setting time
- ST7P models offer a number of timing ranges. Please see Selection Guide below
- Large dial makes time setting easy
- LED indicators make it easy to monitor timer operation
- ST7P series meets UL and CSA standards

Product Selection Guide

Part Number	Description	Voltage	Time Range	Price
ST7P-2A15S-ADC	Mini-DIN on-delay timer with timing range of 0.4s to 5s. Input power is 100-120 VAC. DPDT relay output. UL, CSA, TÜV approved	100-120VAC	0.4 seconds to 5 seconds	\$39.75
ST7P-2A13T-ADC	Mini-DIN on-delay timer with timing range of 2s to 30s. Input power is 100-120 VAC. DPDT relay output. UL, CSA, TÜV approved		2 seconds to 30 seconds	\$39.75
ST7P-2A16T-ADC	Mini-DIN on-delay timer with timing range of 4s to 60s. Input power is 100-120 VAC. DPDT relay output. UL, CSA, TÜV approved		4 seconds to 60 seconds	\$39.75
ST7P-2A11N-ADC	Mini-DIN on-delay timer with timing range of 1 min. to 10 min. Input power is 100-120 VAC. DPDT relay output. UL, CSA, TÜV approved		1 minute to 10 minutes	\$39.75
ST7P-2A16N-ADC	Mini-DIN on-delay timer with timing range of 4 min. to 60 min. Input power is 100-120 VAC. DPDT relay output. UL, CSA, TÜV approved		4 minutes to 60 minutes	\$39.75
ST7P-2DE5S-ADC	Mini-DIN on-delay timer with timing range of 0.4s to 5s. Input power is 24 VDC. DPDT relay output. UL, CSA, TÜV approved	24VDC	0.4 seconds to 5 seconds	\$39.75
ST7P-2DE3T-ADC	Mini-DIN on-delay timer with timing range of 2s to 30s. Input power is 24 VDC. DPDT relay output. UL, CSA, TÜV approved		2 seconds to 30 seconds	\$39.75
ST7P-2DE6T-ADC	Mini-DIN on-delay timer with timing range of 4s to 60s. Input power is 24 VDC. DPDT relay output. UL, CSA, TÜV approved		4 seconds to 60 seconds	\$39.75
ST7P-2DE1N-ADC	Mini-DIN on-delay timer with timing range of 1 min. to 10 min. Input power is 24 VDC. DPDT relay output. UL, CSA, TÜV approved		1 minute to 10 minutes	\$38.75
ST7P-2DE6N-ADC	Mini-DIN on-delay timer with timing range of 4 min. to 60 min. Input power is 24 VDC. DPDT relay output. UL, CSA, TÜV approved		4 minutes to 60 minutes	\$38.75
TP88X2	DIN rail/surface mount socket for ST7P series timers. UL, CSA, TÜV approved	N/A	N/A	\$7.25



Dimensions (timer and socket assembly)



Koyo Digital Timers

Overview

Koyo digital timers offer flexible features at a great price. A large, easy to read display is offered in a small 1/16 DIN size. The large, bright red LED display has a 12 mm character display height which allows it to be seen easily from a distance and at an angle. In addition, set values use a green LED display to differentiate from timing values. Basic function settings are made with digital switches. Detailed settings are selected with digital keys, so operation is easy.

Features

- Tamper-proof: key protection can be set for individual keys to prevent a malfunction or tampering
- Battery-less memory retention: EEPROM is used to retain values in memory, so there is no need for battery maintenance
- Maintenance has been reduced via removable terminals. After wiring, the terminal cover provides a safe barrier for worry-free use
- Power source for a DC sensor: you can source the power for the sensor from the built-in power source which supplies 60 mA at 24 VDC
- Wide operating AC voltage range of 85-264 VAC
- Various types of time ranges: covers ten types of time ranges with times of 0.001 second to 999.9 hours
- Five types of operating modes: settings of on-delay, off-delay, one-shot, accumulation and flicker
- Flush door/panel mounting
- Display of elapsed time/remaining time
- IP65 protective structure: front cover panel is made of a clear membrane, so operation with wet or dirty hands can be worry-free
- Fully CE and UL compliant



KT-V4S-D



KT-V4S-C-D

Product Selection Guide					
Part Number	Description	Number of Digits	Source Voltage	Time Range	Price
KT-V4S-D*	Digital timer with 10 types of time ranges (see specifications). Input power is 100-240 VAC. UL and CSA approved.	4	100-240 VAC	0.001 second to 999.9 hours	\$100.00
KT-V4S-C-D*	Digital timer with 10 types of time ranges (see specifications). Input power is 12-24 VDC. UL and CSA approved		12-24 VDC		\$100.00
Accessories					
Part Number	Description	Price			
PANEL-16	Mounting clip for 1/16th DIN timers and temperature/process controllers, for door (flush) mounting. 5 clips per package	\$12.00			

* Units ship with a panel mounting clip for door (flush) mounting.

Wiring

