

# WAGO Splicing Connectors

## Splicing Connectors 221 Series LEVER-NUTS®

### Overview

The 221 series LEVER-NUTS® adds a lever to WAGO's CAGE CLAMP® technology allowing for easy opening and closing of the cage clamp. This allows you to quickly and easily connect all conductor types of different cross sections using two-, three-, and five-wire connectors. The 221 series connectors accommodate solid, stranded and fine-stranded conductors in two variants from 12-24AWG and 10-20AWG. You can open WAGO's splicing connectors easily and quickly. Opening the levers on the 221 series requires little effort. This means you can connect conductors quickly without any tools! While connecting the conductor, recessed handles on the sides ensure a secure grip on the connector.

### Features

- More compact, user friendly, and can handle 20A or 30A currents
- Available in 2-, 3-, and 5-wire connectors
- Copper conductors only
- Lever technology eliminates tool use
- With the transparent body, it is easy to inspect the strip length and verify the conductor is completely inserted
- You can mix solid and stranded wire types
- Built-in test points
- 2-year warranty



## Inline Splicing Connectors 221 Series LEVER-NUTS®

The 221 series inline splicing connector combines all the trusted advantages of the 221 series splicing connectors into a slim design. Offering unsurpassed simplicity, speed and reliability, the 221 series provides universal conductor connections – with lever technology that eliminates tools – while offering a visibly secure conductor contact.

### Features

- Has all the advantages of the 221 series - compact and can handle up to 20 Amps
- Transparent body makes it easy to inspect the strip length and verify the conductor is completely inserted
- You can mix solid and stranded wire types
- 2-year warranty




## CAGE CLAMP® Technology

As the world leader in spring pressure connection technology, WAGO offers the perfect connection system to meet your specific needs. As early as 1951, WAGO implemented the concept of using spring pressure instead of screws to connect conductors. With the invention of the CAGE CLAMP®, WAGO set new standards and are continually expanding and optimizing.

### Features

- Shorter wiring times reducing labor costs
- Faster commissioning, reducing upfront costs
- Maintenance-free spring pressure connection technology: Greater system uptime and equipment reliability
- Rugged design: can also be used in harsh environments – anywhere in the world
- 2-year warranty





# Splicing Connectors

## Splicing Connectors 221 Series LEVER-NUTS®




**221-412**

| Splicing Connectors 221 Series LEVER-NUTS® |     |         |                                                               |                    |                   |                             |                  |                     |
|--------------------------------------------|-----|---------|---------------------------------------------------------------|--------------------|-------------------|-----------------------------|------------------|---------------------|
| Part Number                                | Qty | Price   | Wire Range                                                    | Number of Openings | Number of Commons | Strip Length                | Wiring Direction | Drawing Link        |
| <b>20 Amp Models</b>                       |     |         |                                                               |                    |                   |                             |                  |                     |
| <a href="#">221-412</a>                    | 100 | \$29.00 | 0.2- 4mm²<br>[24-12 AWG]<br>(Solid/Stranded)                  | 2                  | 1                 | 11mm<br>[0.43in]            | Side-Entry       | <a href="#">PDF</a> |
| <a href="#">221-413</a>                    | 50  | \$18.00 |                                                               | 3                  |                   |                             |                  | <a href="#">PDF</a> |
| <a href="#">221-415</a>                    | 25  | \$14.00 |                                                               | 5                  |                   |                             |                  | <a href="#">PDF</a> |
| <a href="#">221-2401</a>                   | 60  | \$23.00 | 0.2-4mm² [20-12 AWG] Solid<br>0.2-2.5mm² [18-12 AWG] Stranded | 2                  |                   |                             | In-Line          | <a href="#">PDF</a> |
| <b>30 Amp Models</b>                       |     |         |                                                               |                    |                   |                             |                  |                     |
| <a href="#">221-612</a>                    | 50  | \$28.00 | 0.5 - 6mm²<br>[20-10 AWG]<br>(Solid/Stranded)                 | 2                  | 1                 | 12 - 14mm<br>[0.47-0.55 in] | Side-Entry       | <a href="#">PDF</a> |
| <a href="#">221-613</a>                    | 30  | \$20.00 |                                                               | 3                  |                   |                             |                  | <a href="#">PDF</a> |
| <a href="#">221-615</a>                    | 15  | \$17.00 |                                                               | 5                  |                   |                             |                  | <a href="#">PDF</a> |

| Splicing Connectors Specifications 221 Series LEVER-NUTS® |                                                                                                     |         |         |          |         |         |         |
|-----------------------------------------------------------|-----------------------------------------------------------------------------------------------------|---------|---------|----------|---------|---------|---------|
| Part Number                                               | 221-412                                                                                             | 221-413 | 221-415 | 221-2401 | 221-612 | 221-613 | 221-615 |
| UL Rated Voltage<br>(per UL 486C)                         | 600V                                                                                                |         |         |          |         |         |         |
| UL Rated Current<br>(per UL 486C)                         | 20A                                                                                                 |         |         |          | 30A     |         |         |
| IEC Rated Voltage<br>(per EN 60664)                       | 450V                                                                                                |         |         |          |         |         |         |
| IEC Rated Current<br>(per EN 60664)                       | 32A                                                                                                 |         |         |          | 41A     |         |         |
| Temperature Range                                         | Surrounding air temperature: 85°C [-40 to 185°F] / Continuous air temperature: 105°C [-40 to 221°F] |         |         |          |         |         |         |
| Connection Technology                                     | CAGE CLAMP®                                                                                         |         |         |          |         |         |         |
| Connector Conductor Material                              | Copper                                                                                              |         |         |          |         |         |         |
| Housing Material                                          | Polycarbonate(PC)                                                                                   |         |         |          |         |         |         |
| Color - Body                                              | Transparent                                                                                         |         |         |          |         |         |         |
| Color - Actuator                                          | Orange                                                                                              |         |         |          |         |         |         |
| Flammability Class<br>(per UL94)                          | V2                                                                                                  |         |         |          |         |         |         |
| Weight                                                    | 1.7g                                                                                                | 2.5g    | 4g      | 2.4g     | 3g      | 4g      | 7.1g    |
| CE Conformity                                             | CE (EN 60947-1 / EN 60947-7-1)                                                                      |         |         |          |         |         |         |
| Approvals                                                 | cULus E69654 / E201573                                                                              |         |         |          |         |         |         |

# WAGO Splicing Connectors


## Splicing Connectors 221 Series LEVER-NUTS®




Easy to use  
1. Open lever  
2. Insert wire  
3. Close lever

With the transparent body, it is easy to inspect the strip length and verify the conductor is completely inserted.

Wire inserted properly



Wire stripped properly



Two test slots

Easily combine various types and sizes of wires: solid, stranded, and flexible.

221-4 series is rated for 20A with a wire range of 24-12 AWG

221-6 series is rated for 30A with a wire range of 20-10 AWG

