
BALLUFF Capacitive Proximity Sensors

Capacitive Proximity Sensors



- Stainless steel or polybutylene terephthalate housing
- LCP (liquid crystal polymer) active face
- Cable or M12 connector
- PNP or NPN, N.O. or N.C.
- IP66 or IP67 protection



BCS00NA

| Capacitive Proximity Sensor Selection Chart (Tubular) | | | | | | | | | |
|---|----------|----------------------------------|-----------|--------------|---------|----------------------------|-----------------------------|--------------------|--------------|
| Part Number | Price | Sensing Range | Mounting | Output State | Logic | Connection | Housing Material | Data Sheet Link | Drawing Link |
| M12 | | | | | | | | | |
| BCS00P0 | \$136.00 | 4mm [0.16 in] | Flush | N.O. | PNP | 4-pin M12 quick-disconnect | Stainless Steel | PDF | <u>PDF</u> |
| BCS00P1 | \$136.00 | | | N.C. | | | | PDF | <u>PDF</u> |
| BCS00P4 | \$136.00 | 8mm [0.31 in] | Non-flush | | | | | PDF | <u>PDF</u> |
| BCS00PJ | \$100.00 | 4mm [0.16 in] | Flush | N.O. | | | Polybutylene Terephthalate | PDF | <u>PDF</u> |
| BCS00PU | \$102.00 | 411111 [0.16 11] | | | | Cable, 3-pole, 6.5ft/2m | | <u>PDF</u> | <u>PDF</u> |
| BCS00R0 | \$102.00 | | | | | | | PDF | <u>PDF</u> |
| BCS00R1 | \$141.00 | 8mm [0.31 in] | Non-flush | N.C. | | | | <u>PDF</u> | <u>PDF</u> |
| BCS0179 | \$261.00 | 011111 [0.31 111] | | N.O. | | 4-pin M12 quick-disconnect | Stainless Steel | <u>PDF</u> | <u>PDF</u> |
| BCS017A | \$261.00 | | | N.C. | NDN/DND | | | <u>PDF</u> | <u>PDF</u> |
| BCS017K | \$254.00 | F [0 00 :-1 | Flush | N.O. | NPN/PNP | | | PDF | <u>PDF</u> |
| BCS017L | \$254.00 | 5mm [0.20 in] | | N.C. | | | | PDF | <u>PDF</u> |
| M18 | | | | | | | | | |
| BCS006A | \$212.00 | 15mm [0 50 in] | Non-flush | N.O. | PNP | 4-pin M12 quick-disconnect | Stainless Steel | <u>PDF</u> | <u>PDF</u> |
| BCS00LM | \$108.00 | 15mm [0.59 in] | | | | | Polybutylene Terephthalate | <u>PDF</u> | <u>PDF</u> |
| BCS00M8 | \$108.00 | | Flush | | | | | PDF | <u>PDF</u> |
| BCS00MF | \$126.00 | 8mm [0.31 in] | | | | | Stainless Steel | <u>PDF</u> | <u>PDF</u> |
| BCS00MJ | \$108.00 | | | | NPN | | Polybutylene Terephthalate | <u>PDF</u> | <u>PDF</u> |
| BCS00NZ | \$111.00 | | | | PNP | Cable, 3-pole, 6.5ft/2m | | <u>PDF</u> | <u>PDF</u> |
| M30 | | | | | | | | | |
| BCS004K | \$153.00 | 20mm [0.79 in] | Flush | N.O./N.C. | PNP | Cable, 3-pole, 6.5ft/2m | Polybutylene Terephthalate | PDF | <u>PDF</u> |
| BCS004M | \$151.00 | | | | | 4-pin M12 quick-disconnect | | PDF | <u>PDF</u> |
| BCS004T | \$200.00 | | | | | | Stainless Steel | <u>PDF</u> | <u>PDF</u> |
| BCS007F | \$151.00 | | Non-flush | | | | Polybutylene Terephthalate | <u>PDF</u> | <u>PDF</u> |
| BCS007L | \$234.00 | | | | | | Stainless Steel | PDF | <u>PDF</u> |
| BCS00NA | \$109.00 | 15mm [0.59 in] 25mm [0.98 in] | Flush | NO | | | Dalukutulana Tanankii siste | PDF | <u>PDF</u> |
| BCS00NH | \$109.00 | | Non-flush | N.O. | | | Polybutylene Terephthalate | PDF | <u>PDF</u> |

www.automationdirect.com

BALLUFF Capacitive Proximity Sensors

Capacitive Proximity Sensors




- Polyoxymethylene (POM) thermoplastic housing
- LCP (liquid crystal polymer) active face
- Cable or M8 connector
- PNP or NPN, N.O. or N.C.
- IP65 or IP67 protection




| BCS003 | 3K |
|--------|----|
|--------|----|

| Capacitive Proximity Sensor Selection Chart (Round) | | | | | | | | | | | |
|---|----------|----------------|----------|--------------|---------|---------------------------|------------------------|--------------------|--------------|--|--|
| Part Number | Price | Sensing Range | Mounting | Output State | Logic | Connection | Housing Material | Data Sheet Link | Drawing Link | | |
| BCS003K | \$132.00 | 25mm [0.98 in] | Flush | N.O./N.C. | NPN/PNP | Cable, 3-pole, 6.5ft/2m | Polyoxymethylene (POM) | <u>PDF</u> | <u>PDF</u> | | |
| BCS003L | \$129.00 | | | | | 3-pin M8 quick-disconnect | | <u>PDF</u> | <u>PDF</u> | | |

Capacitive Proximity Sensors





- Cable or M8 connector
- PNP or NPN, N.O. or N.C.
- IP67 protection



BCS012A

BCS00TR

| Capacitive Proximity Sensor Selection Chart (Flat) | | | | | | | | | | |
|--|----------|----------------|----------|--------------|---------|---------------------------|----------------------------|--------------------|--------------|--|
| Part Number | Price | Sensing Range | Mounting | Output State | Logic | Connection | Housing Material | Data Sheet Link | Drawing Link | |
| Square | | | | | | | | | | |
| BCS00TR | \$92.00 | 20mm [0.79 in] | Flush | N.O./N.C. | NPN/PNP | Cable, 3-pole, 6.5ft/2m | Polybutylene Terephthalate | PDF | <u>PDF</u> | |
| BCS00U6 | \$92.00 | | | N.O. | PNP | 3-pin M8 quick-disconnect | | PDF | PDF | |
| Rectangular | | | | | | | | | | |
| BCS012A | \$141.00 | 8mm [0.31 in] | Flush | N.O. | PNP - | Cable, 3-pole, 0.9ft/0.3m | Polypropylene (PP) | PDF | <u>PDF</u> | |
| BCS012T | \$143.00 | | | | | 4-pin M8 quick-disconnect | | PDF | <u>PDF</u> | |