

Classic Series Fiberglass Enclosures

Crowned Screw Cover



CL907W

Construction

- Hot compression molded fiberglass reinforced polyester (thermoset)
- Poured polyurethane seamless gasket provides watertight, dust-tight environmental seal
- 304 stainless steel used on all external hardware
- Rounded edges, minimal protrusions or exposed pocket prevents accumulation of dust or debris
- Raised bosses with brass inserts accepting #10-32 screws for optional panel mounting
- Workable material cuts, drills, punches and saws with ease and accuracy
- Four recessed cover screws
- Lift-off cover
- Non-conductive, UV-resistant
- 216 lb-in impact resistance per UL746C
- Smooth surface, no color variations, swirls or color pockets, no voids
- Color: Gray

Listings

- UL/cUL [File E64358]
- NEMA Types 1, 3, 3S, 3R, 4X, and 12 [Files 508A, 50, and 50e]
- CSA Standard C22.2 Types 1, 3, 3S, 3R, 4X, and 12 [File LR069014]
- UL 1741 [File E333478]
- Temperature Range (-76°F to +274°F) (-60°C to +134°C)
- Flammability Rating UL94-5V
- NFPA No. 101 Flame Spread Class A (1)

Certifications

- UL, CSA, CE, REACH
- Outdoor UV Exposure Rated [UL 746C (F1)]



Classic Series Fiberglass Enclosures – Crowned Screw Cover

Part Number	Price	Enclosure Overall Size HxWxD	Wt.	Carbon Steel Subpanel	Fiberglass Subpanel	Aluminum Subpanel	Drawing Link
CL707W	\$247.00	7.21 x 7.21 x 5.09 [183 x 183 x 129]	3.00 [1.36]	BP66CS	—	BP66AL	PDF
CL907W	\$262.00	9.21 x 7.21 x 5.09 [234 x 183 x 129]	4.00 [1.81]	BP86CS	BP86FG	BP86AL	PDF
CL1109W	\$278.00	11.21 x 9.21 x 6.09 [285 x 234 x 155]	5.00 [2.27]	BP108CS	BP108FG	BP108AL	PDF
CL1311W	\$304.00	13.21 x 11.21 x 6.59 [336 x 285 x 167]	7.00 [3.17]	BP1210CS	BP1210FG	BP1210AL	PDF
CL1513W	\$358.00	15.21 x 13.21 x 7.09 [386 x 336 x 180]	9.00 [4.08]	BP1412CS	BP1412FG	BP1412AL	PDF

Notes: Subpanels must be ordered separately.
Dimensions in inches [millimeters].
Weight in pounds [kilograms].

Classic Series Fiberglass Enclosures

Crowned Hinged Screw Cover



CL907HW

Construction

- Hot compression molded fiberglass reinforced polyester (thermoset)
- Poured polyurethane seamless gasket provides watertight, dust-tight environmental seal
- 304 stainless steel used on all external hardware
- Rounded edges, minimal protrusions or exposed pocket prevents accumulation of dust or debris
- Raised bosses with brass inserts accepting #10-32 screws for optional panel mounting
- Workable material cuts, drills, punches and saws with ease and accuracy
- Full length, stainless steel, hinged cover with two recessed cover screws
- Non-conductive, UV-resistant
- 216 lb-in impact resistance per UL746C
- Smooth surface, no color variations, swirls or color pockets, no voids
- Color: Gray

Listings

- UL/cUL [File E64358]
- NEMA Types 1, 3, 3S, 3R, 4X, and 12 [Files 508A, 50, and 50e]
- CSA Standard C22.2 Types 1, 3, 3S, 3R, 4X, and 12 [File LR069014]
- UL 1741 [File E333478]
- Temperature Range (-76°F to +274°F) (-60°C to +134°C)
- Flammability Rating UL94-5V
- NFPA No. 101 Flame Spread Class A (1)

Certifications

- UL, CSA, CE, REACH
- Outdoor UV Exposure Rated [UL 746C (F1)]



Classic Series Fiberglass Enclosures – Crowned Hinged Screw Cover							
Part Number	Price	Enclosure Overall Size HxWxD	Wt.	Carbon Steel Subpanel	Fiberglass Subpanel	Aluminum Subpanel	Drawing Link
<u>CL707HW</u>	\$261.00	7.21 x 7.21 x 5.09 [183 x 183 x 129]	3.00 [1.36]	<u>BP66CS</u>	—	<u>BP66AL</u>	PDF
<u>CL907HW</u>	\$278.00	9.21 x 7.21 x 5.09 [234 x 183 x 129]	4.00 [1.81]	<u>BP86CS</u>	<u>BP86FG</u>	<u>BP86AL</u>	PDF
<u>CL1109HW</u>	\$294.00	11.21 x 9.21 x 6.09 [285 x 234 x 155]	5.00 [2.27]	<u>BP108CS</u>	<u>BP108FG</u>	<u>BP108AL</u>	PDF
<u>CL1513HW</u>	\$379.00	15.21 x 13.21 x 7.09 [386 x 336 x 180]	9.00 [4.08]	<u>BP1412CS</u>	<u>BP1412FG</u>	<u>BP1412AL</u>	PDF
<u>CL1311HW</u>	\$327.00	13.21 x 11.21 x 6.59 [336 x 285 x 167]	7.00 [3.17]	<u>BP1210CS</u>	<u>BP1210FG</u>	<u>BP1210AL</u>	PDF
Notes: Subpanels must be ordered separately. Dimensions in inches [millimeters]. Weight in pounds [kilograms].							

Classic Series Fiberglass Enclosures

Crowned Single-Door with 1/4-Turn Latch



CL707HL

Construction

- Hot compression molded fiberglass reinforced polyester (thermoset)
- Poured polyurethane seamless gasket provides watertight, dust-tight environmental seal
- 304 stainless steel used on all external hardware
- Rounded edges, minimal protrusions or exposed pocket prevents accumulation of dust or debris
- Raised bosses with brass inserts accepting #10-32 screws for optional panel mounting
- Workable material cuts, drills, punches and saws with ease and accuracy
- Hinged cover with 1/4-turn latch
- Full 180° door opening
- Non-conductive, UV-resistant
- 216 lb-in impact resistance per UL746C
- Smooth surface, no color variations, swirls or color pockets, no voids
- Color: Gray

Listings

- UL/cUL [File E64358]
- NEMA Types 1, 3, 3S, 3R, 4X, and 12 [Files 508A, 50, and 50e]
- CSA Standard C22.2 Types 1, 3, 3S, 3R, 4X, and 12 [File LR069014]
- UL 1741 [File E333478]
- Temperature Range (-76°F to +274°F) (-60°C to +134°C)
- Flammability Rating UL94-5V
- NFPA No. 101 Flame Spread Class A (1)

Certifications

- UL, CSA, CE, REACH
- Outdoor UV Exposure Rated [UL 746C (F1)]



Classic Fiberglass Enclosures – Crowned Single-Door with 1/4-Turn Latch

Part Number	Price	Enclosure Overall Size HxWxD	Wt.	No. Latches	Carbon Steel Subpanel	Fiberglass Subpanel	Aluminum Subpanel	Drawing Link
CL707HL	\$373.00	7.21 x 7.21 x 5.09 [183 x 183 x 129]	3.00 [1.36]	1	BP66CS	—	BP66AL	PDF
CL907HL	\$410.00	9.21 x 7.21 x 5.09 [234 x 183 x 129]	4.00 [1.81]	1	BP86CS	BP86FG	BP86AL	PDF
CL1109HL	\$406.00	11.21 x 9.21 x 6.09 [285 x 234 x 155]	5.00 [2.27]	1	BP108CS	BP108FG	BP108AL	PDF
CL1311HL	\$431.00	13.21 x 11.21 x 6.59 [336 x 285 x 167]	7.00 [3.17]	1	BP1210CS	BP1210FG	BP1210AL	PDF
CL1513HL	\$495.00	15.21 x 13.21 x 7.09 [386 x 336 x 180]	9.00 [4.08]	1	BP1412CS	BP1412FG	BP1412AL	PDF

Notes: Subpanels must be ordered separately.
Dimensions in inches [millimeters].
Weight in pounds [kilograms].

Classic Series Fiberglass Enclosures

Crowned Single-Door with Twist-Lock Latch



CL1311HLL

Construction

- Hot compression molded fiberglass reinforced polyester (thermoset)
- Poured polyurethane seamless gasket provides watertight, dust-tight environmental seal
- 304 stainless steel used on all external hardware
- Rounded edges, minimal protrusions or exposed pocket prevents accumulation of dust or debris
- Raised bosses with brass inserts accepting #10-32 screws for optional panel mounting
- Workable material cuts, drills, punches and saws with ease and accuracy
- Hinged cover with twist-lock latches
- Full 180° door opening
- Non-conductive, UV-resistant
- 216 lb-in impact resistance per UL746C
- Smooth surface, no color variations, swirls or color pockets, no voids
- Color: Gray

Listings

- UL/cUL [File E64358]
- NEMA Types 1, 3, 3S, 3R, 4X, and 12 [Files 508A, 50, and 50e]
- CSA Standard C22.2 Types 1, 3, 3S, 3R, 4X, and 12 [File LR069014]
- UL 1741 [File E333478]
- Temperature Range (-76°F to +274°F) (-60°C to +134°C)
- Flammability Rating UL94-5V
- NFPA No. 101 Flame Spread Class A (1)

Certifications

- UL, CSA, CE, REACH
- Outdoor UV Exposure Rated [UL 746C (F1)]



Classic Series Fiberglass Enclosures – Crowned Single-Door with Twist-Lock Latch								
Part Number	Price	Enclosure Overall Size HxWxD	Wt.	No. Latches	Carbon Steel Subpanel	Fiberglass Subpanel	Aluminum Subpanel	Drawing Link
CL1311HLL	\$375.00	13.21 x 11.21 x 6.59 [336 x 285 x 167]	7.00 [3.17]	1	BP1210CS	BP1210FG	BP1210AL	PDF
CL1513HLL	\$459.00	15.21 x 13.21 x 7.09 [386 x 336 x 180]	9.00 [4.08]	2	BP1412CS	BP1412FG	BP1412AL	PDF

Notes: Subpanels must be ordered separately.
 Dimensions in inches [millimeters].
 Weight in pounds [kilograms].

Classic Series Fiberglass Enclosures

Crowned Single-Door with Quick-Release Latch



[CL1513HPL](#)

Construction

- Hot compression molded fiberglass reinforced polyester (thermoset)
- Poured polyurethane seamless gasket provides watertight, dust-tight environmental seal
- 304 stainless steel used on all external hardware
- Rounded edges, minimal protrusions or exposed pocket prevents accumulation of dust or debris
- Raised bosses with brass inserts accepting #10-32 screws for optional panel mounting
- Workable material cuts, drills, punches and saws with ease and accuracy
- Hinged cover with padlockable quick-release latches
- Full 180° door opening
- Non-conductive, UV-resistant
- 216 lb-in impact resistance per UL746C
- Smooth surface, no color variations, swirls or color pockets, no voids
- Color: Gray

Listings

- UL/cUL [File E64358]
- NEMA Types 1, 3, 3S, 3R, 4X, and 12 [Files 508A, 50, and 50e]
- CSA Standard C22.2 Types 1, 3, 3S, 3R, 4X, and 12 [File LR069014]
- UL 1741 [File E333478]
- Temperature Range (-76°F to +274°F) (-60°C to +134°C)
- Flammability Rating UL94-5V
- NFPA No. 101 Flame Spread Class A (1)

Certifications

- UL, CSA, CE, REACH
- Outdoor UV Exposure Rated [UL 746C (F1)]



Classic Series Fiberglass Enclosures – Crowned Single-Door with Quick-Release Latch

Part Number	Price	Enclosure Overall Size HxWxD	Wt.	No. Latches	Carbon Steel Subpanel	Fiberglass Subpanel	Aluminum Subpanel	Drawing Link
<u>CL707HPL</u>	\$305.00	7.21 x 7.21 x 5.09 [183 x 183 x 129]	3.00 [1.36]	1	<u>BP66CS</u>	—	<u>BP66AL</u>	<u>PDF</u>
<u>CL907HPL</u>	\$322.00	9.21 x 7.21 x 5.09 [234 x 183 x 129]	4.00 [1.81]	1	<u>BP86CS</u>	<u>BP86FG</u>	<u>BP86AL</u>	<u>PDF</u>
<u>CL1109HPL</u>	\$339.00	11.21 x 9.21 x 6.09 [285 x 234 x 155]	5.00 [2.27]	1	<u>BP108CS</u>	<u>BP108FG</u>	<u>BP108AL</u>	<u>PDF</u>
<u>CL1311HPL</u>	\$366.00	13.21 x 11.21 x 6.59 [336 x 285 x 167]	7.00 [3.17]	1	<u>BP1210CS</u>	<u>BP1210FG</u>	<u>BP1210AL</u>	<u>PDF</u>
<u>CL1513HPL</u>	\$449.00	15.21 x 13.21 x 7.09 [386 x 336 x 180]	9.00 [4.08]	2	<u>BP1412CS</u>	<u>BP1412FG</u>	<u>BP1412AL</u>	<u>PDF</u>

Notes: Subpanels must be ordered separately.
Dimensions in inches [millimeters].
Weight in pounds [kilograms].