AutomationDirect – GS Series Brake Resistors for AC Drives

GS Series: 80W–9.6 kW Brake Resistors Overview

Automation Direct GS series brake resistors are designed for use with any AC drive up to 600V. See the specifications section of your Automation Direct AC drive manual for the drive-to-resistor cross reference.

Open:

Encapsulated offerings from 80W to 5.0 kW.

Panel mount coil offerings from 750W to 1.5 kW.

Enclosed NEMA1:

Offerings from 1.0 kW to 9.6 kW.



GS-2020-BR-ENC

GS-2020-BR-ENC (cover removed for display)

Drive Usage Cross References

Refer to the online technical specifications below for a list of compatibility between brake resistors and VFDs sold by AutomationDirect.

- For GS4 series drives, see GS4 Drive Braking Components.
- For GS10 series drives, see GS10 Drive Braking Components.
- For GS20(X) series drives, see GS20(X) Drive Braking Components.
- For GS30 series drives, see GS30 Drive Braking Components.
- For Ironhorse ACG series drives, see ACG Drive Braking Components.
- For Ironhorse ACN series drives, see ACN Drive Braking Components.
- For WEG CFW500 series drives, see CFW500 Drive Braking Components.



GS-BR-400W150 (Open Encapsulated)



GS-BR-1K0W020 (Open Panel Coil)

AutomationDirect – GS Series Brake Resistors for AC Drives

GS Series Specifications

Open Type Braking Resistor Specifications							
Туре	Part Number	Price	Power	Resistance (Ω)	Drawing Link	Connection Terminal Type	
Open- Encapuslated Flat Mount	<u>GS-BR-080W200</u>	\$17.00	- 80W -	200	PDF	Wire Leads (150mm length)	
	<u>GS-BR-080W750</u>	\$17.00		750	PDF	whe Leads (150mm length)	
	<u>GS-BR-200W091</u>	\$34.50	200W	91	PDF	Wire Loads (200mm longth)	
	<u>GS-BR-200W360</u>	\$34.50	20070	360	PDF	Wire Leads (200mm length)	
That Would	<u>GS-BR-300W070</u>	\$41.50		70	<u>PDF</u>		
	<u>GS-BR-300W250</u>	\$39.00	300W	250	<u>PDF</u>		
	<u>GS-BR-300W400</u>	\$32.00		400	PDF	Wire Leads (150mm length)	
	<u>GS-BR-400W040</u>	\$49.50	- 400W -	40	<u>PDF</u>		
	<u>GS-BR-400W150</u>	\$46.50		150	PDF		
	<u>GS-BR-500W100</u>	\$38.50	500W	100	<u>PDF</u>	Blade conector	
	<u>GS-BR-750W140</u>	\$68.00	750W	140	PDF	_	
	<u>GS-BR-1K0W4P3</u>	\$110.00	1kW	4.3	<u>PDF</u>		
	<u>GS-BR-1K0W5P1</u>	\$110.00		5.1	PDF		
	<u>GS-BR-1K0W016</u>	\$110.00		16	<u>PDF</u>		
Open- Panel Mount	<u>GS-BR-1K0W020</u>	\$110.00		20	PDF		
Coil	<u>GS-BR-1K0W075</u>	\$110.00		75	<u>PDF</u>		
٩	<u>GS-BR-1K2W3P9</u>	\$121.00	1.2 kW	3.9	PDF	Blade conector	
	<u>GS-BR-1K2W015</u>	\$121.00		15	PDF		
	<u>GS-BR-1K5W3P3</u>	\$144.00	1.5 kW	3.3	<u>PDF</u>		
	<u>GS-BR-1K5W012</u>	\$144.00		12	PDF		
	<u>GS-BR-1K5W013</u>	\$144.00		13	PDF		
	<u>GS-BR-1K5W040</u>	\$125.00		40	PDF		
	<u>GS-BR-1K5W043</u>	\$144.00		43	PDF		

Open Type Brake Resistor General Specifications						
	Test Condition	Specification				
Operating Temperature	_	 Open Encapsulated Flat Mount: -55 to 250 °C (when temp > 200°C use forced cooling with airspeed 3–10m/s) Open Panel Mount Coil: -55 to 600°C (when temp > 350°C, use forced cooling with airspeed 3–10m/s) 				
Tolerance	@25°C ±5%					
Temperature Coefficient	_	±260ppm/°C				
Housing Material	-	Open Encapsulated Flat Mount: Oxidized aluminum Open Panel Mount Coil: Ceramic coating				
Isolation Resistance	Between terminals (terminal wire) and housing or mounting bracket	100M Ω @ 500VDC for 1 minute				
Dielectric Strength	Between terminals (terminal wire) and housing or mounting bracket	1500VAC for 1 minute				
Overload	Cycle 10s on ~90s off	10 x rated power				
Lead Pull Strength	_	2.5 kg for 10 seconds (not applicable when resistor has no leads)				
Vibration	10–55–10 Hz sweep in 1 minute, amplitude 0.75 mm	2 hours per direction				

AutomationDirect – GS Series Brake Resistors for AC Drives

GS Series Specifications, continued

Enclosed Type Braking Resistor Specifications						
Туре	Part Number	Price	Power (kW)	Resistance (Ω)	Drawing Link	Connection Terminal Type
	<u>GS-2010-BR-ENC</u>	\$358.00	1.0	20	PDF	
	GS-2015-BR-ENC	\$621.00	2.4	13.6	PDF	
	GS-2020-BR-ENC	\$689.00	3.0	10	PDF	
	GS-2025-BR-ENC	\$842.00	4.8	8	PDF	
Enclosed NEMA1 with Temperature switch	GS-2030-BR-ENC	\$827.00		6.8	PDF	
remperature switch	GS-2040-BR-ENC	\$689.00	3.0	10	PDF	
	<u>GS-2050-BR-ENC</u>	\$842.00	4.8	8	PDF	
	GS-4015-BR-ENC	\$358.00	1.0	50	PDF	Terminal block
	GS-4020-BR-ENC	\$445.00	1.5	40	PDF	
	<u>GS-4025-BR-ENC</u>	\$1,058.00	4.8	32	PDF	
	<u>GS-4030-BR-ENC</u>	\$1,058.00		27.2	PDF	
	<u>GS-4040-BR-ENC</u>	\$1,058.00	6.0	20	PDF	
	<u>GS-4050-BR-ENC</u>	\$1,246.00	9.6	16	PDF	
	GS-4060-BR-ENC	\$1,246.00		13.6	PDF	
	<u>GS-4075-BR-ENC</u>	\$1,058.00	6.0	20	PDF	
	<u>GS-4100-BR-ENC</u>	\$1,246.00	9.6	13.6	PDF	

Legacy Braking Resistor Specifications								
Туре	Legacy Part Number	Price	Power (W)	Resistance (Ω)	Drawing Link	Replacement Part Number		
Open	<u>GS-20P5-BR</u>	Retired	80	200	PDF	<u>GS-BR-080W200</u>		
	<u>GS-21P0-BR</u>	Retired	80	200	PDF	<u>GS-BR-080W200</u>		
	<u>GS-22P0-BR</u>	Retired	300	100	PDF	n/a		
	<u>GS-23P0-BR</u>	Retired	300	70	<u>PDF</u>	<u>GS-BR-300W070</u>		
	<u>GS-25P0-BR</u>	Retired	400	40	<u>PDF</u>	<u>GS-BR-400W040</u>		
	<u>GS-27P5-BR</u>	Retired	500	30	PDF	n/a		
	<u>GS-41P0-BR</u>	\$26.00	80	750	<u>PDF</u>	<u>GS-BR-080W750</u>		
	<u>GS-42P0-BR</u>	\$58.00	300	400	PDF	<u>GS-BR-300W400</u>		
	<u>GS-43P0-BR</u>	Retired	300	250	<u>PDF</u>	<u>GS-BR-300W250</u>		
	<u>GS-45P0-BR</u>	\$70.00	400	150	PDF	<u>GS-BR-400W150</u>		
	<u>GS-47P5-BR</u>	\$70.00	500	100	<u>PDF</u>	<u>GS-BR-500W100</u>		
	<u>GS-4010-BR</u>	Retired	1.0 kW	75	<u>PDF</u>	<u>GS-BR-1K0W075</u>		