NEMA 3R, 4, 4X, 12, and 13 Stainless **Steel Two-Door Freestanding HAMMOND** MANUFACTURING. **Disconnect with Slope Top**





Applications

- · Designed to house electrical, electronic, hydraulic or pneumatic controls and instruments.
- Provides protection where equipment may be hosed down or otherwise be very wet, or in specific applications where corrosion is a serious problem.

Construction

- Formed 12-gauge 304 stainless steel.
- Flange trough collar (FTC) around odor opening excludes liquids and contaminants.
- · Heavy-duty lifting eyes are anchored into reinforced top corners.
- · Removable doors are secured with bullet-style, heavy duty, lift off hinges.
- Formed 10-gauge steel inner panel is provided on collar studs.
- · Panel supports are provided.
- Center post is removable, providing easy panel installation.
- Heavy-duty three-point latching mechanism with heavy-duty roller ends is provided for ease of door closing.
- Uses 1/4 turn latch handles.
- Seamless poured-in-place gasket.
- Right hand master door handle complete with screwdriver defeater and padlock hasp.
- · Additional door handle complete with padlock hasp.
- · A mechanical interlock activated by the master door prevents the auxiliary door from being opened first.
- The pre-installed flange cutout provides mounting for disconnect operators (verify compatibility in advance) - interlock hardware included with enclosure.
- · A provision for mounting fluorescent lighting is provided.
- A bonding stud is provided in the door and a grounding stud is provided in the enclosure for each door.
- A literature pocket is provided for the inside of the door.

Finish

 Enclosure and cover are finished in ANSI 61 gray powder coating.

Listings

- UL 508A Type 3R, 4X, and 12 [File E65324]
- CSA Type 3R, 4, 4X, and 12 [File LR21001]
- · Complies with:
- NEMA Type 3R, 4X, 12, and 13
- IEC 60529, IP66









Enclosure Accessories Locks and Latches



1/4-Turn Latch Handles



Features

- Durable zinc diecast or stainless steel.
- Removable handle stop for clockwise / counter-clockwise operation.
- Textured powder coat Black finish on zinc cast handle.
- Maintains NEMA rating of enclosure.
- Padlock "trigger" design for security requirements.
- Optional key lock or defeater available. Key lock versions include two keys.

1/4-Turn Latch Handles							
Part Number	Price	Security Type	Latch Points	Material	Finish	For Use With These Hammond Enclosures Only	Drawing Link
MHK1	\$127.00	padlocking	1	die-cast zinc	black matte	single-door NEMA 4 and NEMA 12	PDF
MHKD1	\$133.00	padlocking with defeater					PDF
MHKL1	\$144.00	combination keylocking/ padlocking					PDF
MHK2	\$217.00	padlocking	3	die-cast zinc	black matte	less than 60in (H) NEMA 4 and NEMA 12	<u>PDF</u>
MHKD2	\$228.00	padlocking with defeater					<u>PDF</u>
MHKL2	\$246.00	combination keylocking/ padlocking					PDF
MHK3	\$221.00	padlocking	3	die-cast zinc	black matte	60in (H) or greater NEMA 4 and NEMA 12	PDF
MHKD3	\$232.00	padlocking with defeater					PDF
MHKL3	\$251.00	combination keylocking/ padlocking					PDF
MHK1SS	\$234.00	padlocking	1	316 stainless steel	#4 brush	single-door NEMA 4X	<u>PDF</u>
MHKD1SS	\$258.00	padlocking with defeater					PDF
MHKL1SS	\$258.00	combination keylocking/ padlocking					PDF
MHK2SS	\$249.00	padlocking	3	316 stainless steel	#4 brush	less than 60in (H) NEMA 4X	<u>PDF</u>
MHKD2SS	\$274.00	padlocking with defeater					<u>PDF</u>
MHKL2SS	\$274.00	combination keylocking/ padlocking					PDF
MHK3SS	\$362.00	padlocking	3	316 stainless steel	#4 brush	60in (H) or greater NEMA 4X	<u>PDF</u>
MHKD3SS	\$398.00	padlocking with defeater					PDF
MHKL3SS	\$398.00	combination keylocking/ padlocking					PDF

www.automationdirect.com Enclosure Hardware tENH-178