Adjustable Depth Cable Manager

Features

- · Constructed of 16-gauge steel.
- Prevents cables from sagging when running front to rear.
- Universal design compatible with both racks and cabinets.
- Cable pass-through holes are evenly spaced.
- · Easily mounts to EIA mounting rails.
- Cable tie-off slots help keep cables managed.
- Requires two pairs of mounting rails to install.
- Finished in smooth black powder coat.
- · Requires mounting hardware.

Listings

• TAA compliant for GSA Schedule purchases.



| Adjustable Depth Cable Manager | | | | | | | | |
|---|---------|---------------|----------------------|-----------|-----------------|--|--|--|
| Part Number | Price | Rack Units | Depth Range | Height | Drawing Link | | | |
| RDCM2136BK | \$75.00 | 2U | 21.5-36.5 [546-927] | 3.00 [76] | PDF | | | |
| RDCM3348BK | \$83.00 | 2U | 33.5-48.5 [851-1232] | 3.00 [76] | PDF | | | |
| Note: Dimensions in inches [millimeters]. | | | | | | | | |

Rackmount Adjustable Angle Bracket

Application

The Rackmount Adjustable Angle Bracket (RAAB) is designed to support the weight of non rack-mounted heavy equipment.

It is also useful for non-rack-mounted equipment. Available in two depth ranges, the RAAB can support up to 200 lb [91 kg] and can adjust from 24 in [610 mm] to 48 in [914 mm] in depth.



| Rackmount Adjustable Angle Bracket | | | | | | | | | |
|---|----------|---------------|------------------|-----------|-----------------|--|--|--|--|
| Part Number | Price | Rack Units | Depth Range | Height | Drawing Link | | | | |
| RAAB2436BK | \$83.00 | 1U | 24-36 [610-914] | 1.72 [44] | PDF | | | | |
| RAAB3648BK | \$100.00 | 1U | 36-48 [914-1219] | 1.72 [44] | PDF | | | | |
| Note: Dimensions in inches [millimeters]. | | | | | | | | | |

Features

- Constructed from 16-gauge steel.
- Angles mount to 19 in [483 mm], 23 in [584 mm] or 24 in [610 mm] EIA rack mounting rails
- Requires two pairs of mounting rails.
- Designed to support equipment such as servers, switch gear, and a computer/server chassis on its side.
- Free-floating design easily adjusts in depth to accommodate different equipment dimensions.
- Two adjustable depth options.
- Sold in pairs.
- Finished in smooth black powder coat.
- Requires mounting hardware.
- Tested to nearly double the suggested load rating of 200 lb [91 kg].