

Disconnect Handle Applications for Freestanding and Floor-Mount Painted Steel Disconnect Enclosures



Designed to house the following available at AutomationDirect.com

- AutomationDirect.com NEMA 1/12 Flexible shaft handle for Molded Case Circuit Breakers (MCCBs). Series F_S0_C flex handle mechanisms are available in four sizes to actuate all AutomationDirect MCCBs from 15 amps up to 600 amps. **F0S03C, F0S06C, F1S03C, F1S06C, F3S03C, F3S06C, F4S04C, and F4S06C.** Requires operator adapter plate kit **AKU**.
- Socomec Disconnect switches with cable, flange-mounted cable operator and handles. Handles **37299002** and **37299003**, cable operator **37299903**, and cables **37299992** (3ft) or **37299993** (5ft). Requires operator adapter plate kit **AKU**.
- Fuji Electric NEMA 12 flexible shaft handle for Molded Case Circuit Breakers (MCCBs). Series BW9F flex handle mechanisms are available in four sizes to actuate all Fuji Electric MCCBs from 15 Amps to 800 Amps. **BW9F0CA-15A, BW9F0CA-20A, BW9F0GA-15A, BW9F0GA-20A, BW9F0HA-15A, BW9F0HA-20A, BW9F0JA-15A, and BW9F0JA-20A.** Requires operator adapter panel kit **AKU**.
- Gladiator Molded Case Circuit Breakers (MCCBs) flange mounted cable operator and handles. See Gladiator sections for handles and cable options. **GCBX1-FHC-N3R4-M, GCBX1-FHC-N4X-M, GCBX5-FHC-N3R4-M, and GCBX5-FHC-N4X-M**

Available at AutomationDirect.com

Disconnect Enclosure Series	AutomationDirect F_S0_C Series	Socomec 37299002 and 37299003	Fuji BW9F Series	Gladiator GCBX
2U_D_FFTC Series	✓	✓	✓	✓
2UDPC_FFTC Series	✓	✓	✓	✓
UHD_FTC Series	✓	✓	✓	✓
Note: Each of these Disconnect enclosures requires an AKU Operator Adapter Kit from AutomationDirect.				


Designed to house other brands

- Allen-Bradley Bulletin 1494V and 140U disconnect switches with flange-mounted variable-depth operating mechanisms and Bulletin 1494V flange-mounted variable-depth operating mechanisms for circuit breakers. Requires operator adapter plate kit **AKU**.
- Allen-Bradley** Bulletin 1494F flange-mounted disconnect switches and Bulletin 149D flange-mounted operators for circuit breakers. Requires operator adapter plate kit **AK1494FD**.
- ABB** Controls flange-mounted variable-depth operating mechanisms for disconnect switches and circuit breakers. Requires operator adapter plate kit **AKU**.
- Eaton / Cutler-Hammer** Type C361 flange-mounted variable-depth operating mechanisms with disconnect switches and Type C371 flange-mounted variable depth operating mechanisms for circuit breakers; also Flex Shaft™ handle mechanisms for circuit breakers. Requires operator adapter plate kit **AKU**.
- General Electric** Type STDA flange handles and variable depth operating mechanisms for disconnect switches and circuit breakers; also Spectra Flex™ cable operators for circuit breakers. Requires operator adapter plate kit **AKU**.
- SIEMENS** I-T-E Max-Flex flange-mounted variable depth operating handle for disconnect switches and circuit breakers. Requires operator adapter plate kit **AKU**.
- Square D** Class 9422 disconnect switches with flange-mounted variable depth operating mechanisms or cable Industry Standards mechanisms and Class 9422 flange-mounted variable depth operating mechanisms or cable mechanisms for circuit breakers. These enclosures will not accept Square D Class 9422 bracket-mounted disconnect devices, Class 9422TG1, or TG2 devices. Requires operator adapter plate kit **AKU**.

Other Brands

Disconnect Enclosure Series	Square D 9422 Series	Allen-Bradley 1494F and 1494D Series*	Allen-Bradley 1494V and 140U Series	ABB Controls	Eaton/ Cutler-Hammer C361 and C371 Series	General Electric STDA Series	Siemens I-T-E Max-Flex Series
2U_FFTC Series	✓	✓	✓	✓	✓	✓	✓
2UDPC_FFTC Series	✓	✓	✓	✓	✓	✓	✓
UHD_FTC Series	✓	✓	✓	✓	✓	✓	✓
Note: Each of these Disconnect enclosures requires an AKU Operator Adapter Kit from AutomationDirect.							
*Requires AK1494FD Adapter Kit from AutomationDirect.							

NEMA 3R, 4, 4X, 12, and 13 Stainless Steel Freestanding Disconnect



Note: Disconnect switches, circuit breakers and operators are not provided with the enclosure, and must be ordered separately from the manufacturer.

Applications

Designed to house the following safety disconnect equipment:

- ABB Controls flange mounted variable depth operating mechanisms for disconnect switches and circuit breakers.
- Allen Bradley 1494V and 1494U variable depth flange mounted disconnect switches and circuit breaker mechanisms. NOT COMPATIBLE WITH 1494V-R1, R2, W2 operating handles nor with Allen Bradley 1494F flange mounted disconnect switches and 1494D flange mounted operators for circuit breakers.
- C-H Westinghouse type C361 disconnect switches and operator mechanism. Cutler Hammer Type C371 circuit breaker operating mechanisms. Flex-Shaft™ handle operators for circuit breakers.
- General Electric type STDA flange handles and variable depth operating mechanisms for disconnect switches and circuit breakers. Also Spectra-Flex™ cable operators for circuit breakers.
- Siemens I-T-E Max-Flex™ flange mounted variable depth operating handles for disconnect switches and circuit breakers.
- Square D disconnect switches and circuit breakers used with Class 9422 flange mounted variable depth operating mechanisms or cable mechanisms. These enclosures will not receive Class 9422 bracket mounted disconnect devices or class 9422TG1 or TG2 devices. NOT COMPATIBLE WITH Class 9422 bracket mounted devices nor Class 9422TG1/TG2 devices.

Construction

- Formed from 12-gauge 304 stainless steel with smooth, continuously welded seams.
- Body stiffeners are provided in the larger enclosures for extra rigidity.
- Flange trough collar (FTC) around door opening excludes liquids and contaminants.
- Heavy duty lifting eyes are anchored into reinforced top corners.
- Removable doors are secured with heavy duty lift-off hinges.
- Formed 10-gauge steel subpanels are provided on collar studs.
- Panel supports are provided.

- Center post is removable, providing easy panel installation.
- Heavy duty 3-point latching mechanism with heavy duty roller ends is provided for ease of door closing.
- Uses 1/4 turn latch handles.
- Oil-resistant gaskets are permanently secured.
- The right-hand door on all enclosures is the master door.
- Master door handle complete with screw defeater and padlock hasp.
- Slave door handle complete with padlock hasp.
- A mechanical interlock activated by the master door prevents the auxiliary door from being opened first.
- The pre-installed flange cutout provides mounting for disconnect operators (verify compatibility in advance) — interlock hardware included with enclosure.
- A provision for mounting fluorescent lighting is provided.
- A bonding stud is provided in the door, and a grounding stud is provided in the enclosure for each door.
- A literature pocket is provided for the inside of the door.

Finish

- Door and enclosure are natural stainless steel with a #4 smooth, brushed finish..
- Subpanel(s) is finished RAL9003 white powder coating.

Listings

- UL 508A Type 4, 12, and 13 [UL File E65324]
- CSA Type 4, 12, and 13 [CSA File LR21001]
- Complies with
 - NEMA Type 3R, 4, 4X, 12, and 13
 - IEC 60529, IP54
- Appropriate components are required to maintain these standards.



NEMA 3R, 4, 4X, 12, and 13 Stainless Steel Freestanding Disconnect



Single-Door				
Part Number	Price	Enclosure Size HxWxD	Included Subpanel HxW	Drawing Link
1UHD722918N4SS	5,867.00	72.13 x 28.50 x 19.35 [1832 x 724 x 491]	60.00 x 21.75 [1524 x 552]	PDF
1UHD723518N4SS	6,509.00	72.13 x 28.75 x 19.35 [1832 x 730 x 491]	60.00 x 27.75 [1524 x 705]	PDF
1UHD724118N4SS	7,156.00	72.13 x 34.75 x 19.35 [1832 x 883 x 491]	60.00 x 33.75 [1524 x 857]	PDF
1UHD844118N4SS	7,932.00	84.13 x 40.75 x 19.35 [2137 x 1035 x 491]	72.00 x 33.75 [1829 x 857]	PDF
1UHD844124N4SS	8,124.00	84.13 x 40.75 x 25.35 [2137 x 1035 x 644]	72.00 x 33.75 [1829 x 857]	PDF
1UHD904118N4SS	8,310.00	90.13 x 40.75 x 19.35 [2289 x 1035 x 491]	78.00 x 33.75 [1981 x 857]	PDF
1UHD904120N4SS	8,637.00	90.13 x 40.75 x 21.35 [2289 x 1035 x 542]	78.00 x 33.75 [1981 x 857]	PDF
1UHD904124N4SS	9,160.00	90.13 x 40.75 x 25.35 [2289 x 1035 x 644]	78.00 x 33.75 [1981 x 857]	PDF

Note: Dimensions in inches [millimeters].

Two-Door				
Part Number	Price	Enclosure Size HxWxD	Included Subpanel HxW	Drawing Link
2UHD725518N4SS	10,315.00	72.13 x 40.75 x 19.35 [1832 x 1035 x 491]	60.00 x 48.00 [1524 x 1219]	PDF
2UHD726718N4SS	11,611.00	72.13 x 55.00 x 19.35 [1832 x 1397 x 491]	60.00 x 60.00 [1524 x 1524]	PDF
2UHD727918N4SS	12,925.00	72.13 x 67.00 x 19.35 [1832 x 1702 x 491]	60.00 x 72.00 [1524 x 1829]	PDF
2UHD727924N4SS	13,914.00	72.13 x 79.00 x 25.35 [1832 x 2007 x 644]	60.00 x 72.00 [1524 x 1829]	PDF
2UHD847918N4SS	14,305.00	84.13 x 79.00 x 19.35 [2137 x 2007 x 491]	72.00 x 72.00 [1829 x 1829]	PDF
2UHD847924N4SS	14,743.00	84.13 x 79.00 x 25.35 [2137 x 2007 x 644]	72.00 x 72.00 [1829 x 1829]	PDF
2UHD907918N4SS	14,977.00	90.13 x 79.00 x 19.35 [2289 x 2007 x 491]	78.00 x 72.00 [1981 x 1829]	PDF
2UHD907920N4SS	15,461.00	90.13 x 79.00 x 21.35 [2289 x 2007 x 542]	78.00 x 72.00 [1981 x 1829]	PDF
2UHD907924N4SS	16,146.00	90.13 x 79.00 x 25.35 [2289 x 2007 x 644]	78.00 x 72.00 [1981 x 1829]	PDF

Note: Dimensions in inches [millimeters].

Three-Door					
Part Number	Price	Enclosure Size HxWxD	Included Subpanel 1 HxW	Included Subpanel 2 HxW	Drawing Link
3UHD7210118N4SS	15,957.00	72.13 x 100.25 x 19.35 [1832 x 2546 x 491]	60.00 x 72.00 [1524 x 1829]	60.00 x 27.75 [1524 x 705]	PDF
3UHD7211918N4SS	17,969.00	72.13 x 118.25 x 19.35 [1832 x 3004 x 491]	60.00 x 72.00 [1524 x 1829]	60.00 x 33.75 [1524 x 857]	PDF
3UHD8411918N4SS	19,876.00	84.13 x 118.25 x 19.35 [2137 x 3004 x 491]	72.00 x 72.00 [1829 x 1829]	72.00 x 33.75 [1829 x 857]	PDF
3UHD8411924N4SS	20,499.00	84.13 x 118.25 x 25.35 [2137 x 3004 x 644]	72.00 x 72.00 [1829 x 1829]	72.00 x 33.75 [1829 x 857]	PDF
3UHD9011924N4SS	22,344.00	90.13 x 118.25 x 25.35 [2289 x 3004 x 644]	72.00 x 72.00 [1829 x 1829]	72.00 x 33.75 [1829 x 857]	PDF

Note: Dimensions in inches [millimeters].


Four-Door				
Part Number	Price	Enclosure Size HxWxD	Included Subpanels HxW	Drawing Link
4UHD8415718N4SS	23,350.00	84.13 x 156.50 x 19.35 [2137 x 3975 x 491]	(2) 72.00 x 72.00 [1829 x 1829]	PDF
4UHD9015718N4SS	27,310.00	90.13 x 156.50 x 19.35 [2289 x 3975 x 491]	(2) 72.00 x 72.00 [1829 x 1829]	PDF

Note: Dimensions in inches [millimeters].

NEMA 3R, 4, 4X, 12, and 13 Stainless Steel Freestanding Disconnect



Dimensions



Enclosure Accessories

Locks and Latches



1/4-Turn Latch Handles



Features

- Durable zinc diecast or stainless steel.
- Removable handle stop for clockwise / counter-clockwise operation.
- Textured powder coat Black finish on zinc cast handle.
- Maintains NEMA rating of enclosure.
- Padlock "trigger" design for security requirements.
- Optional key lock or defeater available. Key lock versions include two keys.

1/4-Turn Latch Handles							
Part Number	Price	Security Type	Latch Points	Material	Finish	For Use With These Hammond Enclosures Only	Drawing Link
MHK1	127.00	padlocking	1	die-cast zinc	black matte	single-door NEMA 4 and NEMA 12	PDF
MHKD1	133.00	padlocking with defeater					PDF
MHKL1	144.00	combination keylocking/ padlocking					PDF
MHK2	217.00	padlocking	3	die-cast zinc	black matte	less than 60in (H) NEMA 4 and NEMA 12	PDF
MHKD2	228.00	padlocking with defeater					PDF
MHKL2	246.00	combination keylocking/ padlocking					PDF
MHK3	221.00	padlocking	3	die-cast zinc	black matte	60in (H) or greater NEMA 4 and NEMA 12	PDF
MHKD3	232.00	padlocking with defeater					PDF
MHKL3	251.00	combination keylocking/ padlocking					PDF
MHK1SS	234.00	padlocking	1	316 stainless steel	#4 brush	single-door NEMA 4X	PDF
MHKD1SS	258.00	padlocking with defeater					PDF
MHKL1SS	258.00	combination keylocking/ padlocking					PDF
MHK2SS	249.00	padlocking	3	316 stainless steel	#4 brush	less than 60in (H) NEMA 4X	PDF
MHKD2SS	274.00	padlocking with defeater					PDF
MHKL2SS	274.00	combination keylocking/ padlocking					PDF
MHK3SS	362.00	padlocking	3	316 stainless steel	#4 brush	60in (H) or greater NEMA 4X	PDF
MHKD3SS	398.00	padlocking with defeater					PDF
MHKL3SS	398.00	combination keylocking/ padlocking					PDF