30mm Pushbutton with 2.5 in Hole Spacing NEMA 12 and 13 Wall-Mount



Applications

Designed to hold 30mm [1.18 in] oil-tight pushbuttons, switches and pilot lights with extra size to allow 2.5 in [63.5 mm] between centers of pushbutton holes. Provides protection from dirt, dust, oil and water.

Construction

- Fabricated from 14-gauge steel
- Closed-cell oil-resistant neoprene gasket
- Continuously-welded seams ground smooth
- Cover held in place by continuous hinge
- Subpanel included with enclosure
- External mounting feet, top and bottom of enclosure
- Captivated cover screws thread into sealed wells
- Standard "4-way" pushbutton holes accept all brands of oil-tightpushbuttons, witches and pilot lights
- · Grounding provisions provided

WIEGWANN[®]

Finish

- ANSI 61 gray polyester powder inside and out over phosphatized surfaces
- Included subpanels are white polyester powder over phosphatized surfaces

Listings

- UL 508 12 and 13 [UL File E64791]
- NEMA/EEMAC 12 and 13





| 30mm Pushbutton with 2.5 in Hole Spacing NEMA 12 and 13 Wall-Mount | | | |
|--|----------|---------|--|
| Part Number | Price | # Holes | Enclosure Size HxWxD |
| PBYX4S | \$172.00 | 4 | 8.82 x 7.88 x 6.33 [224 x 200 x 161] |
| PBYX6 | \$202.00 | 6 | 11.32 x 7.88 x 6.33 [288 x 200 x 161] |
| PBYX9 | \$236.00 | 9 | 11.32 x 10.38 x 6.33 [288 x 264 x 161] |
| PBYX12 | \$267.00 | 12 | 13.82 x 10.38 x 6.33 [351 x 264 x 161] |
| PBYX16 | \$304.00 | 16 | 13.82 x 12.88 x 6.33 [351 x 327 x 161] |
| PBYX20 | \$341.00 | 20 | 16.32 x 12.88 x 6.33 [415 x 327 x 161] |
| PBYX25 | \$384.00 | 25 | 16.32 x 15.38 x 6.33 [415 x 391 x 161] |
| PBYX30 | \$418.00 | 30 | 18.82 x 15.38 x 6.33 [478 x 391 x 161] |
| PBYX36 | \$473.00 | 36 | 18.82 x 17.88 x 6.33 [478 x 454 x 161] |
| PBYX42 | \$518.00 | 42 | 21.32 x 17.88 x 6.33 [542 x 454 x 161] |
| Note: Dimensions in inches [millimeters]. | | | |

30mm Pushbutton with 2.5 in Hole Spacing NEMA 12 and 13 Wall-Mount



Dimensions





PBYX HOLE ARRANGEMENTS

