

G-Series ISO 15552 Pneumatic Cylinders – 80mm Bore 80mm Bore, Double-acting, Magnetic Piston, Cushions



NITRA pneumatic ISO 15552 interchangeable cylinder, 80mm bore, 25mm diameter piston rod, G3/8 (BSPP) female ports, double acting; flange, pivot and clevis mount options available. Adjustable cushions on both ends. See the end of the section for accessory details.

Features

• Adjustable cushions

- Internal magnet for sensor switching
- Three sides with longitudinal slots for inserting and securing retractable sensors such as type CPS9F and CPS9Q (see position switches at the end of the cylinder section for further details)
- G (BSPP) threaded ports

80mm bore,	double	acting, ta	oped end	caps
Part Number	Price	Stroke Length (mm)	"A" (mm [inch])	Weight (lb)
<u>G80M025MD-MC</u>	\$131.00	25	153 [6.02]	6.9
<u>G80M050MD-MC</u>	\$135.00	50	178 [7.01]	7.4
<u>G80M075MD-MC</u>	\$139.00	75	203 [7.99]	7.9
<u>G80M100MD-MC</u>	\$142.00	100	228 [8.98]	8.4
<u>G80M125MD-MC</u>	\$148.00	125	253 [9.96]	8.9
<u>G80M150MD-MC</u>	\$152.00	150	278 [10.94]	9.4
<u>G80M200MD-MC</u>	\$160.00	200	328 [12.91]	10.4
G80M250MD-MC	\$172.00	250	378 [14.88]	11.4
<u>G80M300MD-MC</u>	\$181.00	300	428 [16.85]	12.4
<u>G80M400MD-MC</u>	\$197.00	400	528 [20.79]	14.4
<u>G80M500MD-MC</u>	\$216.00	500	628 [24.72]	16.4
<u>G80M600MD-MC</u>	\$233.00	600	728 [28.66]	18.4

Specific	ations
Aluminum body and end caps	Plastoferrite magnet
C45 chromed piston rod	NBR (Nitrile Butadiene Rubber) buffer + static o-rings
Die cast aluminum head	NBR (Nitrile Butadiene Rubber) cushioning gasket
NBR (Nitrile Butadiene Rubber) piston and piston rod gasket	Brass cushioning needle with needle out movement safety system
Steel guide bushing with bronze and PTFE (Teflon) insert	Pressure rating 145 psi [10 bar], AIR ONLY
Drawn anodized aluminum body	Temperature rating 14°F to 176°F
Aluminum piston with PTFE (Teflon) pad	[-10°C to 80°C]
Extend force at 100 psi = 779.1 lb.	Retract force at 100 psi = 703.0 lb.

BSPP = British Standard Pipe Parallel


* The cushions decelerate the piston rod over the last mm (approx.) of stroke and are adjustable. Cushioned cylinders have an adjustable orifice and pre-lubricated nitrile cushion seal.

Mounting Acce	Mounting Accessories							
Style	Part No.							
Foot Mount	GMB-80MM							
Front or Rear Flange	GFL-80MM							
Male Rear Clevis	<u>GMC-80MM</u>							
Spherical Male Clevis	GSMC-80MM							

Rod Accessories							
Style	Part No.						
Rod Clevis	<u>GRC-M20-15</u>						
Rod Eye	<u>GRE-M20-15</u>						
Self Aligning Rod Coupler	<u>GRCP-M20-15</u>						
Rod Nut	<u>GN-M20-15</u>						

Dimensions

mm [inches]



See our website www.AutomationDirect.com for complete Engineering drawings.

94.0 [3.70]



G-Series ISO 15552 Pneumatic Cylinders – Accessories

	D-Series Heavy Duty Pneumatic Cylinder Acces	sories			
Part Number	Description	Pcs/Pkg	Wt (lb)	Drawing Link	Price
<u>GRC-M10-125</u>	Rod clevis, M10 X 1.25 thread, zinc plated steel. For use with NITRA G-series cylinders.	1	0.2	PDF	\$4.50
<u>GRC-M12-125</u>	Rod clevis, M12 X 1.25 thread, zinc plated steel. For use with NITRA G-series cylinders.	1	0.3	PDF	\$7.50
<u>GRC-M16-15</u>	Rod clevis, M16 X 1.5 thread, zinc plated steel. For use with NITRA G-series cylinders.	1	0.8	PDF	\$16.00
<u>GRC-M20-15</u>	Rod clevis, M20 X 1.5 thread, zinc plated steel. For use with NITRA G-series cylinders.	1	1.5	PDF	\$26.00
<u>GRE-M10-125</u>	Rod eye, M10 X 1.25 thread, spherical bearing, zinc plated steel. For use with NITRA G-series cylinders.	1	0.2	<u>PDF</u>	\$25.00
<u>GRE-M12-125</u>	Rod eye, M12 X 1.25 thread, spherical bearing, zinc plated steel. For use with NITRA G-series cylinders.	1	0.3	<u>PDF</u>	\$28.50
<u>GRE-M16-15</u>	Rod eye, M16 X 1.5 thread, spherical bearing, zinc plated steel. For use with NITRA G-series cylinders.	1	0.5	PDF	\$53.00
<u>GRE-M20-15</u>	Rod eye, M20 X 1.5 thread, spherical bearing, zinc plated steel. For use with NITRA G-series cylinders.	1	0.9	PDF	\$71.00
<u>GRCP-M10-125</u>	Self-aligning rod coupler, M10 X 1.25 thread, zinc plated steel. For use with NITRA G-series cylinders.	1	0.5	PDF	\$57.00
<u>GRCP-M12-125</u>	Self-aligning rod coupler, M12 X 1.25 thread, zinc plated steel. For use with NITRA G-series cvlinders.	1	0.7	PDF	\$60.00
<u>GRCP-M16-15</u>	Self-aligning rod coupler, M16 X 1.5 thread, zinc plated steel. For use with NITRA G-series cylinders.	1	1.4	PDF	\$78.00
<u>GRCP-M20-15</u>	Self-aligning rod coupler, M20 X 1.5 thread, zinc plated steel. For use with NITRA G-series cylinders.	1	1.5	PDF	\$96.00
GMB-32MM	Foot mount bracket, zinc plated steel. For use with 32mm bore NITRA G-series cylinders.	1	0.2	PDF	\$7.00
GMB-40MM	Foot mount bracket, zinc plated steel. For use with 40mm bore NITRA G-series cylinders.	1	0.3	PDF	\$8.25
GMB-50MM	Foot mount bracket, zinc plated steel. For use with 50mm bore NITRA G-series cylinders.	1	0.4	PDF	\$9.50
GMB-63MM	Foot mount bracket, zinc plated steel. For use with 63mm bore NITRA G-series cylinders.	1	0.6	PDF	\$10.50
GMB-80MM	Foot mount bracket, zinc plated steel. For use with 80mm bore NITRA G-series cylinders.	1	1.0	PDF	\$15.00
<u>GMB-100MM</u>	Foot mount bracket, zinc plated steel. For use with 100mm bore NITRA G-series cylinders.	1	1.3	PDF	\$24.00
GMC-32MM	Rear pivot eye, zinc plated steel. For use with 32mm bore NITRA G-series cylinders.	1	0.2	PDF	\$18.00
GMC-40MM	Rear pivot eye, zinc plated steel. For use with 40mm bore NITRA G-series cylinders.	1	0.3	PDF	\$19.00
GMC-50MM	Rear pivot eye, zinc plated steel. For use with 50mm bore NITRA G-series cylinders.	1	0.6	PDF	\$22.00
<u>GMC-63MM</u>	Rear pivot eye, zinc plated steel. For use with 63mm bore NITRA G-series cylinders.	1	0.9	PDF	\$26.00
<u>GMC-80MM</u>	Rear pivot eye, zinc plated steel. For use with 80mm bore NITRA G-series cylinders.	1	1.5	PDF	\$32.00
<u>GMC-100MM</u>	Rear pivot eye, zinc plated steel. For use with 100mm bore NITRA G-series cylinders.	1	2.4	PDF	\$44.50
<u>GSMC-32MM</u>	Rear spherical pivot, spherical bearing, zinc plated steel. For use with 32mm bore NITRA G-series cylinders.	1	0.3	PDF	\$25.00
GSMC-40MM	Rear spherical pivot, spherical bearing, zinc plated steel. For use with 40mm bore NITRA G-series cylinders.	1	0.4	PDF	\$27.00
GSMC-50MM	Rear spherical pivot, spherical bearing, zinc plated steel. For use with 50mm bore NITRA G-series cylinders.	1	0.5	PDF	\$39.00
<u>GSMC-63MM</u>	Rear spherical pivot, spherical bearing, zinc plated steel. For use with 63mm bore NITRA G-series cylinders.	1	0.7	PDF	\$50.00
GSMC-80MM	Rear spherical pivot, spherical bearing, zinc plated steel. For use with 80mm bore NITRA G-series cylinders.	1	1.3	PDF	\$62.00
GSMC-100MM	Rear spherical pivot, spherical bearing, zinc plated steel. For use with 100mm bore NITRA G-series cylinders.	1	1.9	PDF	\$84.00
<u>GFL-32MM</u>	Flange mount plate, zinc plated steel. For use with 32mm bore NITRA G-series cylinders.	1	0.5	PDF	\$12.00
GFL-40MM	Flange mount plate, zinc plated steel. For use with 40mm bore NITRA G-series cylinders.	1	0.6	PDF	\$13.00
GFL-50MM	Flange mount plate, zinc plated steel. For use with 50mm bore NITRA G-series cylinders.	1	1.2	PDF	\$16.00
<u>GFL-63MM</u>	Flange mount plate, zinc plated steel. For use with 63mm bore NITRA G-series cylinders.	1	1.5	PDF	\$23.00
<u>GFL-80MM</u>	Flange mount plate, zinc plated steel. For use with 80mm bore NITRA G-series cylinders.	1	3.1	PDF	\$26.00
<u>GFL-100MM</u>	Flange mount plate, zinc plated steel. For use with 100mm bore NITRA G-series cylinders.	1	4.5	PDF	\$31.00
<u>GN-M10-125</u>	Rod nut, M10 X 1.25 thread, zinc plated steel. For use with NITRA G-series cylinders.	1	0.2	PDF	\$1.50
<u>GN-M12-125</u>	Rod nut, M12 X 1.25 thread, zinc plated steel. For use with NITRA G-series cylinders.	1	0.2	PDF	\$1.75
<u>GN-M16-15</u>	Rod nut, M16 X 1.5 thread, zinc plated steel. For use with NITRA G-series cylinders.	1	0.2	PDF	\$2.00
<u>GN-M20-15</u>	Rod nut, M20 X 1.5 thread, zinc plated steel. For use with NITRA G-series cylinders.	1	0.2	PDF	\$2.25




G-Series ISO Pneumatic Cylinders – Accessories

Rod Clevis



Part no. GRC-M10-125





Note: Comes with Pivot Pin installed.


Rod Clevis Dimension Table										
Part #	A	В	С	D	Ε	F	G	Н		
<u>GRC-M10-125</u>	20.00 [0.78]	10.00 [0.39]	10.00 [0.39]	26.00 [1.02]	10.00 [0.39]	40.00 [1.57]	52.00 [2.04]	M10x1.25		
<u>GRC-M12-125</u>	24.00 [0.94]	12.00 [0.47]	24.00 [0.94]	32.00 [1.25]	12.00 [0.47]	48.00 [1.88]	62.00 [2.44]	M12x1.25		
<u>GRC-M16-15</u>	32.00 [1.25]	16.00 [0.62]	32.00 [1.25]	40.00 [1.57]	16.00 [0.62]	64.00 [2.51]	83.00 [3.26]	M16x1.5		
<u>GRC-M20-15</u>	40.00 [1.57]	20.00 [0.78]	40.00 [1.57]	48.00 [1.88]	20.00 [0.78]	80.00 [3.14]	105.00 [4.13]	M20x1.5		

Rod Eye



Dimensions

mm [inches]








Rod Eye Dimension Table										
Part #	A	В	С	D	Ε	F	G	H	1	
<u>GRE-M10-125</u>	28.00 [1.10]	14.00 [0.55]	15.00 [0.59]	10.50 [0.41]	10.00 [0.39]	43.00 [1.69]	57.00 [2.24]	M10x1.25	19 [0.74]	
<u>GRE-M12-125</u>	32.00 [1.25]	16.00 [0.62]	17.00 [0.66]	12.00 [0.47]	12.00 [0.47]	50.00 [1.96]	66.00 [2.59]	M12x1.25	19 [0.74]	
<u>GRE-M16-15</u>	42.00 [1.65]	21.00 [0.82]	22.00 [0.86]	15.00 [0.59]	16.00 [0.62]	64.00 [2.51]	85.00 [3.34]	M16x1.5	22 [0.86]	
<u>GRE-M20-15</u>	50.00 [1.96]	25.00 [0.98]	26.00 [1.02]	18.00 [0.70]	20.00 [0.78]	77.00 [3.03]	102.00 [4.01]	M20x1.5	27 [1.06]	

See our website www.AutomationDirect.com for complete Engineering drawings.








Self Aligning Rod Coupler Dimension Table											
Part #	A	В	C	D	Ε	F	G	H	Ι	J	
<u>GRCP-M10-125</u>	M10x1.25	20.00 [0.78]	20.00 [0.78]	71.00 [2.79]	4.00 [0.15]	22.00 [0.86]	30.00 [1.18]	30.00 [1.18]	19.00 [0.74]	17.00 [0.66]	
<u>GRCP-M12-125</u>	M12x1.25	24.00 [0.94]	20.00 [0.78]	75.00 [2.95]	4.00 [0.15]	22.00 [0.86]	30.00 [1.18]	30.00 [1.18]	19.00 [0.74]	19.00 [0.74]	
<u>GRCP-M16-15</u>	M16x1.5	32.00 [1.25]	32.00 [1.25]	103.00 [4.05]	4.00 [0.15]	32.00 [1.25]	41.00 [1.61]	41.00 [1.61]	30.00 [1.18]	24.00 [0.94]	
<u>GRCP-M20-15</u>	M20x1.5	40.00 [1.57]	40.00 [1.57]	119.00 [4.68]	4.00 [0.15]	32.00 [1.25]	41.00 [1.61]	41.00 [1.61]	30.00 [1.18]	30.00 [1.18]	

Foot Mount Bracket



mm [inches]

Dimensions



Part no. GMB-32MM

Note: Individually packed with 2 screws

						_					
	Foot Mount Dimension Table										
Part #	A	В	C	D	Ε	F	G	Н			
<u>GMB-32MM</u>	7.00	32.00	11.00	4.00	24.00	32.00	45.00	32.5			
	[0.27]	[1.25]	[0.43]	[0.15]	[0.94]	[1.25]	[1.77]	[1.28]			
<u>GMB-40MM</u>	9.00	36.00	15.00	4.00	28.00	36.00	52.00	38.0			
	[0.35]	[1.41]	[0.59]	[0.15]	[1.10]	[1.41]	[2.04]	[1.50]			
<u>GMB-50MM</u>	9.00	45.00	15.00	4.00	32.00	45.00	52.00	46.5			
	[0.35]	[1.77]	[0.59]	[0.15]	[1.25]	[1.77]	[2.04]	[1.83]			
<u>GMB-63MM</u>	9.00	50.00	15.00	6.00	32.00	50.00	75.00	56.5			
	[0.35]	[1.96]	[0.59]	[0.23]	[1.25]	[1.96]	[2.95]	[2.22]			
<u>GMB-80MM</u>	12.00	63.00	20.00	6.00	41.00	63.00	95.00	63.0			
	[0.47]	[2.48]	[0.78]	[0.23]	[1.61]	[2.48]	[3.74]	[2.48]			
<u>GMB-100MM</u>	14.00	71.00	25.00	6.00	41.00	75.00	115.00	89.0			
	[0.55]	[2.79]	[0.98]	[0.23]	[1.61]	[2.95]	[4.52]	[3.50]			

See our website www.AutomationDirect.com for complete Engineering drawings.

CYLINDER MOUNT

B ł




G-Series ISO Pneumatic Cylinders – Accessories

Rear Pivot Eye



Dimensions

mm [inches]



Part no. GMC-32MM



Note: Supplied with 4 screws, 4 washers


		lale Rear	Clevis Di	mension	Table		
Part #	A	В	С	D	Ε	F	G
<u>GMC-32MM</u>	26.00	22.00	10.00	12.00	11.00	33.00	45.00
	[1.02]	[0.86]	[0.39]	[0.47]	[0.43]	[1.29]	[1.77]
<u>GMC-40MM</u>	28.00	25.00	12.00	15.00	13.00	38.00	52.00
	[1.10]	[0.98]	[0.47]	[0.59]	[0.51]	[1.49]	[2.04]
<u>GMC-50MM</u>	32.00	27.00	12.00	15.00	13.00	40.00	65.00
	[1.25]	[1.06]	[0.47]	[0.59]	[0.51]	[1.57]	[2.55]
<u>GMC-63MM</u>	40.00	32.00	16.00	20.00	17.00	49.00	75.00
	[1.57]	[1.25]	[0.62]	[0.78]	[0.66]	[1.92]	[2.95]
<u>GMC-80MM</u>	50.00	36.00	16.00	20.00	17.00	53.00	95.00
	[1.96]	[1.41]	[0.62]	[0.78]	[0.66]	[2.08]	[3.74]
<u>GMC-100MM</u>	60.00	41.00	20.00	25.00	21.00	62.00	115.00
	[2.36]	[1.61]	[0.78]	[0.98]	[0.82]	[2.44]	[4.52]

Spherical Rear Pivot



Dimensions

mm [inches]



Part no. <u>GSMC-32MM</u>

Note: Supplied with 4 screws, 4 washers

	Spherical Male Clevis Dimension Table										
Part #	A	В	С	D	Ε	F	G				
<u>GSMC-32MM</u>	14.00	22.00	10.00	12.00	16.00	38.00	45.00				
	[0.55]	[0.86]	[0.39]	[0.47]	[0.62]	[1.49]	[1.77]				
<u>GSMC-40MM</u>	16.00	25.00	12.00	15.00	19.00	44.00	52.00				
	[0.62]	[0.98]	[0.47]	[0.59]	[0.74]	[1.73]	[2.04]				
<u>GSMC-50MM</u>	16.00	27.00	12.00	15.00	19.00	46.00	65.00				
	[0.62]	[1.06]	[0.47]	[0.59]	[0.74]	[1.81]	[2.55]				
<u>GSMC-63MM</u>	21.00	32.00	16.00	20.00	24.00	56.00	75.00				
	[0.82]	[1.25]	[0.62]	[0.78]	[0.94]	[2.20]	[2.95]				
<u>GSMC-80MM</u>	21.00	36.00	16.00	20.00	24.00	60.00	95.00				
	[0.82]	[1.41]	[0.62]	[0.78]	[0.94]	[2.36]	[3.74]				
GSMC-100MM	25.00	41.00	20.00	25.00	30.00	71.00	115.00				
	[0.98]	[1.61]	[0.78]	[0.98]	[1.18]	[2.79]	[4.52]				

See our website www.AutomationDirect.com for complete Engineering drawings.



G-Series ISO Pneumatic Cylinders – Accessories


Front or Rear Flange



Part no. GFL-32MM

Dimensions

mm [inches]





Note: Supplied with 4 screws


	Fron	t or Rear	Flange	Dimensio	on Table		
Part #	A	В	C	D	Ε	F	G
<u>GFL-32MM</u>	80.00	50.00	10.00	32.00	7.00	32.00	64.00
	[3.14]	[1.96]	[0.39]	[1.25]	[1.25]	[1.25]	[2.52]
<u>GFL-40MM</u>	90.00	55.00	10.00	36.00	9.00	40.00	72.00
	[3.54]	[2.16]	[0.39]	[1.41]	[0.35]	[1.57]	[2.83]
<u>GFL-50MM</u>	110.00	65.00	12.00	45.00	9.00	50.00	90.00
	[4.33]	[2.55]	[0.47]	[1.77]	[0.35]	[1.96]	[3.54]
<u>GFL-63MM</u>	120.00	75.00	12.00	50.00	9.00	63.00	100.00
	[4.72]	[2.95]	[0.47]	[1.96]	[0.35]	[2.48]	[3.93]
<u>GFL-80MM</u>	153.00	95.00	16.00	63.00	12.00	80.00	126.00
	[6.02]	[3.74]	[0.62]	[2.48]	[0.47]	[3.14]	[4.96]
<u>GFL-100MM</u>	178.00	115.00	16.00	75.00	14.00	100.00	150.00
	[7.00]	[4.52]	[0.62]	[2.95]	[0.55]	[3.93]	[5.90]

Rod Nut



Dimensions mm [inches]





Rod Nut Dimension Table				
Part #	A	В	С	
<u>GN-M10-125</u>	M10x1.25	17.00 [0.66]	6.00 [0.23]	
<u>GN-M12-125</u>	M12x1.25	19.00 [0.74]	7.00 [0.27]	
<u>GN-M16-15</u>	M16x1.5	24.00 [0.94]	8.00 [0.31]	
<u>GN-M20-15</u>	M20x1.5	30.00 [1.18]	9.00 [0.35]	

See our website www.AutomationDirect.com for complete Engineering drawings.

1-800-633-0405



CPS Series Cylinder Position Switches

Position Switch Cross Reference Chart				
NITRA Switch Type	Cylinder Brand (may fit some of these cylinders)	Photo Example	Groove Illustration	
CPS CPSF	NITRA A-Series NITRA D-Series NITRA F-Series		Round Cylinder Adapter & Band (CPSG Series)	
CPS9C	DE-STA-CO Robohand SMC Compact Air Bimba Fabco		2.53 Min. +/- 0.1 + R2.13 +/- 0.05	
CPS9D	NITRA L-Series Fabco Numatics Rotomation			
CPS9E	NITRA L-Series Fabco Numatics Rotomation			
CPS9F	NITRA G-Series Fabco Festo Numatics Rotomation			
СРЅ9Н	NITRA E-Series NITRA H-Series			
СРЅ9М	Norgren		5.1 +/-0.1 5.1 +/-0.1 R 3.25	
CPS9Q	NITRA L-Series NITRA G-Series Parker Fabco Festo Numatics Rotomation			