

Continuous Flexing IE Cable

Continuous Flexing Industrial Ethernet Cable Selection									
Part Number	Wiring Standard	Jacket Color	Shield	No. of Pairs	Pair Colors	Description	Approximate Weight (lb/ft)	Minimum Cut Length (ft)*	Price per foot
<u>Q5772-1</u>	Cat5e	Teal	Unshielded	2	Pair 1 - White/Orange & Orange Pair 2 - White/Green & Green	industrial Ethernet cable, unshielded, 2 twisted pairs, 24 AWG, 7/32-stranded, tinned copper, HDPE conductor insulation material, FR-TPE jacket, teal, cut to length.	0.02	20	\$0.70
<u>Q5752-1</u>				4	Pair 1 - White/Blue & Blue Pair 2 - White/Orange & Orange Pair 3 - White/Green & Green Pair 4 - White/Brown & Brown	industrial Ethernet cable, unshielded, 4 twisted pairs, 24 AWG, 7/32-stranded, tinned copper, HDPE conductor insulation material, FR-TPE jacket, teal, cut to length.	0.03		\$0.81
<u>Q5025-1</u>			Foil and Braid	2	Pair 1 - Orange & White/Orange Pair 2 - Green & White/Green	industrial Ethernet cable, shielded, 2 twisted pairs, 24 AWG, 7/32-stranded, tinned copper, HDPE conductor insulation material, FR-TPE jacket, teal, cut to length.	0.04		\$1.34
<u>Q5090-1</u>				4	Pair 1 - Blue & White/Blue Pair 2 - Orange & White/Orange Pair 3 - Green & White/Green Pair 4 - Brown & White/Brown	industrial Ethernet cable, shielded, 4 twisted pairs, 24 AWG, 7/32-stranded, tinned copper, HDPE conductor insulation material, FR-TPE jacket, teal, cut to length.	0.05		\$1.46
<u>Q5026-1</u>	6/6a	Black	Foil and Braid	4	Pair 1 - Blue & White/Blue Pair 2 - Orange & White/Orange Pair 3 - Green & White/Green Pair 4 - Brown & White/Brown	industrial Ethernet cable, shielded, 4 twisted pairs, 26 AWG, 7-stranded, tinned copper, polyethylene conductor insulation material, TPE jacket, teal, cut to length.	0.04		\$1.66
<u>Q5919-1</u>						Cat6/6a industrial Ethernet cable, shielded, 4 twisted pairs, 26 AWG, 7-stranded, tinned copper, HDPE conductor insulation material, polyurethane jacket, black, cut to length.	0.03		\$1.72
<u>Q5922-1</u>		Teal				industrial Ethernet cable, shielded, 4 twisted pairs, 24 AWG, 7-stranded, tinned copper, polyethylene conductor insulation material, TPE jacket, teal, cut to length.	0.05		\$1.77
<u>Q5936-1</u>		Black				Cat6/6a industrial Ethernet cable, shielded, 4 twisted pairs, 24 AWG, 7-stranded, tinned copper, HDPE conductor insulation material, polyurethane jacket, black, cut to length.	0.05		\$1.92



* See web store for maximum cut lengths



Please Note: Our prices on Continuous Flexing IE Cable are closely tied to the market price for copper. This allows us to offer the best savings possible if conditions are favorable; however, it also means that our prices may increase if market conditions warrant.

Continuous Flexing IE Cable - Cat6/6a - Shielded

Continuous Flexing Shielded Cat6/6a Industrial Ethernet Cable Specifications		
	Physical Properties	
	<u>Q5919-1</u>	<u>Q5936-1</u>
Conductor Gauge and Stranding	26 AWG 7/34 stranded tinned copper, 4 twisted pairs	24 AWG 7/32 stranded tinned copper; 4 twisted pairs
Assembly	Individual conductors twisted into pairs, cabled; overall foil and tinned copper braid shield, polyurethane jacket	
Jacket	Black, polyurethane	
Jacket Insulation Thickness	0.022 inch; Nominal	
Shield	Overall shield of 38 AWG tinned copper braid (80% coverage) and aluminized polyester foil shield (100% coverage)	
Cable Overall Diameter	0.239 inch; Nominal	0.291 inch; Nominal
Temp/Voltage	75°C (167°F)/300V	
Minimum Temperature Rating	-40°C (-40°F)	
Plenum	No	
Sunlight Resistant	Yes	
Conductor Insulation	High Density Polyethylene (HDPE)	
Color Code	Pair 1	Blue/White & Blue
	Pair 2	Orange/White & Orange
	Pair 3	Green/White & Green
	Pair 4	Brown/White & Brown
Bare Conductor Diameter	0.019 inch; Nominal	0.0236 inch; Nominal
Conductor Insulation Thickness	0.009 inch; Nominal	0.011 inch; Nominal
Insulated Conductor Diameter	0.036 inch; Nominal	0.046 inch; Nominal
Pair Diameter	0.072 inch; Nominal	0.092 inch; Nominal
Cabled Core Diameter	0.176 inch; Nominal	0.228 inch; Nominal
Shield + Cabled Core Diameter	0.195 inch; Nominal	0.247 inch; Nominal
Print Legend	QUABBIN DATAMAX EXTREME HIGH FLEX INDUSTRIAL ETHERNET/IP PATCH CORD CAT 6/6a SF/UTP P/N 5919 4PR 26AWG -- U.S. PATENT NO. US 8,487,184 B2 -- RoHS -- (LOT DESIGNATOR) (SEQUENTIAL FOOTAGE)	QUABBIN DATAMAX EXTREME HIGH FLEX INDUSTRIAL ETHERNET/IP CAT 6/6a SF/UTP PATCH CORD P/N 5936 4PR 24 AWG -- U.S. PATENT NO. US 8,487,184 B2 -- CAT 6a TIA-568.2-D -- RoHS -- (LOT DESIGNATOR) (SEQUENTIAL FOOTAGE)



Four Pair Shielded

Continuous Flexing IE Cable - Cat6/6a - Shielded

Continuous Flexing Shielded Cat6/6a Industrial Ethernet Cable Specifications		
	Electrical Characteristics (for 100 meters of cable)	
	Q5919-1	Q5936-1
Impedance (1-100 MHz)	100Ω ±15Ω (1-100 MHz), 100 ± 20 Ω 100 - 500 MHz	
Capacitance	13.5 pF/ft @ 1MHz; Nominal	
Resistance (max)	42.6 Ω DC per 1000ft	26.2 Ω DC per 1000ft
Voltage Rating (max)	300V	
Dielectric Withstand, Min.	1500V RMS	
Return Loss	$1 \leq f < 10 \text{ MHz}$ 20 + 6 LOG (f) dB MIN* $10 \leq f < 20 \text{ MHz}$ 26 dB MIN* $20 \leq f \leq 100 \text{ MHz}$ 26 - 5 LOG(f/20) dB MIN* $100 \leq f \leq 500 \text{ MHz}$ 25 - 8.6 LOG(f/20) dB MIN	
Near End Crosstalk (NEXT)	$1 \leq f \leq 500 \text{ MHz}$ 44.3 - 15 LOG(f/100) dB MIN	
Power Sum Near End Crosstalk (PSNEXT)	$1 \leq f \leq 500 \text{ MHz}$ 42.3 - 15 LOG(f/100) dB MIN	
Power Sum Attenuation to Crosstalk Ratio, Far End (PSACRF)	$1 \leq f \leq 500 \text{ MHz}$ 24.8 - 20 LOG(f/100) dB MIN	
Attenuation Crosstalk Ratio, Far End (ACRF)	$1 \leq f \leq 500 \text{ MHz}$ 27.8 - 20 LOG(f/100) dB MIN	
Insertion Loss	$1 \leq f \leq 500 \text{ MHz}$ $1.5[1.82 \sqrt{f} + 0.0091(f) + 0.25/\sqrt{f}] \text{ dB MAX}$	$1 \leq f \leq 500 \text{ MHz}$ $1.2[1.82 \sqrt{f} + 0.0091(f) + 0.25/\sqrt{f}] \text{ dB MAX}$
Delay	$1 \leq f \leq 500 \text{ MHz}$ 534 + 36/√f ns Max	
Delay Skew	$1 \leq f \leq 500 \text{ MHz}$ <45ns	
PS ANEXT LOSS (6 AROUND 1)	$1 \leq f \leq 500 \text{ MHz}$ 62.5 - 15 LOG(f/100) dB 50-500 MHz, 67 dB 1-50MHz	
PS AFEXT (6 AROUND 1)	$1 \leq f \leq 500 \text{ MHz}$ 38.2 - 20 LOG(f/100) dB	
Coupling Attenuation Per IEC 62153-4-9	$30 \leq f \leq 250 \text{ MHz}$ 100 - 20 LOG(f) MAX 60dB E3* Segregation class d acc. EN 50174-2	
Velocity Of Propagation	68%	
Tested Length	100 meters off the reel	
Agency Approvals	CE, RoHS compliant	

* Per ODVA Volume 2 EtherNet/IP

NOTE: All testing conducted off the reel.



Industrial Ethernet Cable

Quabbin DataMax® Extreme Industrial Ethernet Cable *



Features

- Available in Category 5e and 6/6a
- In compliance with TIA 568-C.2 and TIA 1005
- Designed for use in EtherNet/IP systems **
- 26 AWG & 24AWG stranded or 22 AWG solid
- 2 or 4 twisted pairs
- Unshielded or overall braid and foil shields
- Rugged jacket for excellent chemical, moisture, and flame resistance, and exceptional low temperature flexibility
- UL Type CMX OUTDOOR – CM and UL AWM Style 2463 (80°C, 600V)
- Cut to length in 1 foot increments
- Low 20 foot minimum length
- Made in the USA

* DataMax is a registered trademark of Quabbin Wire and Cable Corporation.

** EtherNet/IP is a trademark of ODVA, Inc.

Many industrial applications expose cables to hazards not present in commercial data cabling installations. Although a cable suited for commercial applications may initially work in a harsh industrial environment, it could quickly fail when used in an industrial applications. While commercial grade cables may have a low initial product cost, downtime due to premature failure can be avoided by using a cable that is specifically designed and tested for industrial applications.

Quabbin DataMax Extreme Industrial Ethernet cable jackets were developed to survive the many industrial hazards that commercial jackets will not.

Furthermore, commercial ethernet cables have a tube jacket surrounding the conductor pairs with room within for the pairs to move around and even untwist in flexing applications resulting in early mechanical or electrical failure of the cable.

DataMax Extreme continuous flexing cable jackets are pressure extruded over the cable core, effectively "locking" the conductor pairs in place. This type of jacket construction provides very stable electrical performance, even when the cable is impacted, bent, or repeatedly flexed. Pressure extrusion also provides a very smooth, round, and firm jacket profile that is crush resistant and ideal for obtaining a reliable termination and seal when installing connectors.

Quabbin has performed extensive testing on their pressure extruded jacketed DataMax Extreme Continuous Flexing Industrial Ethernet cables. Samples are subjected to 10 million cycles in a flex testing device that simulates an unsupported bend, simulating a situation the cable would be exposed to on a robotic arm. The unsupported bend test is much more abusive than a C-Track or Tick-tock test, both of which add protection to the cable by supporting the bend. Quabbin DataMax Extreme Industrial Ethernet cable provides superior design and construction that will withstand the rigors of continuous flexing applications and the harsh environments found in industrial installations. Quabbin DataMax Extreme Continuous Flexing Industrial Ethernet cable performs above industry standards, thereby reducing downtime and increasing productivity.

DataMax Extreme Industrial Ethernet cables fully comply with TIA 568-C.2 and TIA 1005 industrial communication specifications and are designed for use in EtherNet/IP systems.

Description

AutomationDirect offers Quabbin DataMax Extreme Industrial Ethernet cable in 2 and 4 pair, unshielded and shielded constructions. Conductors are color coded high density polyethylene insulation. Shielded constructions include both a tinned copper braid shield and aluminized polyester foil overall shield. All constructions feature a rugged jacket with excellent moisture, chemical, UV and weathering resistance, exceptional low-temperature flexibility, and good flame and fire resistance. Some are specifically designed and constructed for continuous flexing applications. The DataMax Extreme Continuous Flexing cables have been tested for a minimum of 1 million cycles (10x cable O.D. minimum radius), a minimum of 10 million cycles (20x cable O.D. minimum radius), and a minimum of 3 million cycles torsion test. Agency approvals include UL Type CMX OUTDOOR - CM, and UL AWM Style 2463 (80°C, 600V).

Click on the above thumbnail or go to
<https://www.automationdirect.com/VID-WD-0016>
 for a short introduction on our cut to length cable

