



Audible Signal Devices

Wall-mount Signal Horns

Features

- Wall mounting
- Continuous tone
- 148mm diameter

| 570 Series Signal Horns Specifications | | |
|--|---|-----------------------------|
| Part Number | 57005255 | 57005267 |
| Price | \$135.00 | \$113.00 |
| Drawing Link | PDF | PDF |
| Description | Signal Horn | |
| Voltage | 24VDC | 115VAC |
| Current Consumption | 350mA | 200mA |
| Tone Frequency | 150Hz | 100Hz (supply frequency) |
| Maximum Volume | 108dB @ 1m | |
| Tone Type | Continuous | |
| Life Duration | > 250h | |
| Operating Temperature | -20 to 60°C [-4 to 140°F] | |
| Protection | IP55 | |
| Weight | 880g [31.04 oz] | 860g [30.34 oz] |
| Housing Material | ABS/PC | |
| Connection | Screwable con max. 2.5 mm² single wire, 18-14 AWG | |
| Agency Approvals | CE, RoHS | |

To obtain the most current agency approval information, see the Agency Approval Checklist section on the specific part number's web page.





Audible Signal Devices

Wall-mount Signal Horns

Features

- Corrosion-resistant aluminum housing, salt water proof
- Wall mounting
- Continuous tone
- 132mm diameter



| 571 Series Signal Horns Specifications | | |
|--|--|-----------------------------|
| Part Number | 57105255 | 57105267 |
| Price | \$421.00 | \$384.00 |
| Drawing Link | PDF | PDF |
| Description | Signal Horn | |
| Voltage | 24VDC | 115VAC |
| Current Consumption | 350mA | 200mA |
| Tone Frequency | 150Hz | 100Hz (supply frequency) |
| Maximum Volume | 108dB @ 1m | |
| Tone Type | Continuous | |
| Life Duration | > 250h | |
| Operating Temperature | -20 to 60°C [-4 to 140°F] | |
| Protection | IP55 | |
| Weight | 880g [31.04 oz] | 860g [30.34 oz] |
| Housing Material | Aluminum | |
| Connection | Screwable con max. 2.5 mm ² single wire, 18-14 AWG | |
| Agency Approvals | CE, RoHS | |

To obtain the most current agency approval information, see the Agency Approval Checklist section on the specific part number's web page.



Features

- Modern electro-mechanical design
- Wall mounting
- Continuous tone
- 178mm diameter



| 573 Series Signal Horns Specifications | | |
|--|---|-----------------------------|
| Part Number | 57300055 | 57300067 |
| Price | \$183.00 | \$145.00 |
| Drawing Link | PDF | PDF |
| Description | Signal Horn | |
| Voltage | 24VDC | 115VAC |
| Current Consumption | 350mA | 200mA |
| Tone Frequency | 150Hz | 100Hz (supply frequency) |
| Maximum Volume | 105dB @ 1m | |
| Tone Type | Continuous | |
| Life Duration | > 250h | |
| Operating Temperature | -30 to 50°C [-22 to 122°F] | |
| Protection | IP65 | |
| Weight | 1200g [42.33 oz] | 1150g [40.57 oz] |
| Housing Material | Polycarbonate/ABS-blend | |
| Connection | Screwable con max. 2.5 mm ² single wire, 18-14 AWG | |
| Agency Approvals | CE, RoHS | |

To obtain the most current agency approval information, see the Agency Approval Checklist section on the specific part number's web page.