

29.00  
[1.14]


93.00  
[3.66]

105.80  
[4.17]

56.25  
[2.21]

382.90±0.50  
[15.07±0.02]

76.00  
[2.99]



10.00<sup>+0.036</sup><sub>0.000</sub>  
[0.39] KEYWAY

10.00<sup>0.000</sup><sub>-0.036</sub>  
[0.39] KEY

10.00 [0.39] X 8.00 [0.31]  
X 60.00 [2.36] KEY

44.50  
[1.75]

4X  
R115.00  
[4.53]

5.00  
[0.20]


Ø 114.30<sup>0.000</sup><sub>-0.025</sub>  
[4.50]

180.00  
[7.09]

Ø 35.00<sup>0.000</sup><sub>-0.018</sub>  
[1.38]  
SHAFT

4X  
Ø 13.50  
[0.53]

Ø 200.00±0.50  
[7.87±0.02]  
B.C.



LS ELECTRIC MEDIUM INERTIA AC BRUSHLESS SERVO MOTOR, 5.5 kW, 3-PHASE, INTEGRATED BRAKE, FOR USE WITH L7PA050U-AD 5 kW DRIVE

APM-FF55DMK2

AutomationDirect.com  
1-800-633-0405



3rd  
ANGLE

NOT TO  
SCALE

PART DIMENSIONS MAY DIFFER SLIGHTLY  
DUE TO MANUFACTURER'S VARIANCES

METRIC UNITS USED  
FOR PART DESIGN

UNLESS OTHERWISE  
SPECIFIED UNITS ARE:

mm  
[inch]

LATEST VERSION  
8/17/2022

SHEET 1 OF 1