


**PRODUCT DESCRIPTION:**

**SDM\_K10**


**PRODUCT CODE:**

**SDM2K10X11**



**DYNAMIC 3D VIEW:**



**STATIC 3D VIEW:**



TECHNICAL VIEW:



## DETAILS:

Part Number	SDM2K10X11
Casing Material	Painted zamak
Width [mm]	50
Electrical connections	Three cable inlets for 1/2"NPT cable glands
IP Degree of Protection	IP66
Actuating Head	90° turnable head with separated actuator
Head Material	Thermoplastic head
Microswitch	Non-overlapping slow action contacts ( 1NO + 1NC )
Approvals	IMQ - cULus - CCC - CSA - EAC
Reference Directives	2014/35/UE - 2006/42/CE
Reference Standards	IEC 60947-5-1 / EN 60947-5-1 / EN ISO 14119
Interlock type according to EN ISO 14119	Type 2
Encoding level according to EN ISO 14119	Low
Operating Temperatures [°C]	-25°C ... +70°C
Stock Temperatures [°C]	-30°C ... +80°C
Protection against electric shocks (according to IEC 60536) [Class]	Class I
Rated Insulating Voltage Ui [V]	500
Pollution Degree	3
Contact rating secondo UL50	A300 - Q300
Rated Impulsive Voltage Uimp [kV]	6
Conventional thermal current in air free Ith (θ min 40 ° C) [A]	10
Short circuit protection (EU min 500Vac - fuses type gG (gl)) [A]	10
Operating currents Ie - AC-15 (50-60 Hz) according to IEC 60947-5-1	24V - 10A / 120V - 6A / 400V - 4A
DC-13 operating currents according to IEC 60947-5-1	24V - 6A / 125V - 0.55A / 250V - 0.4A
Switching Frequency [cycles/hour]	3600
Resistance Between Contacts [mΩ]	25
Connecting Terminals	M3.5 screw with cable clamp (+,-) pozidriv 2
Connecting Cables Dimensions [mm²]	0.75 ... 2.5

### PRODUCT DRAWING RELEASE:

Datasheet creation date: 23/01/2023 13:59

Last Modification (geometry): 14/08/2020 06:16



tel. +39 039 9906408  
+39 039 9903468  
fax +39 039 9906203



Via Novarino 9/L  
23899 Robbiate (LC)  
ITALY



www.comepi.it  
comepi@comepi.it  
tecnico@comepi.it

**DETAILS:**

<b>Protective Conductor Terminal</b>	<b>M3.5 screw with cable clamp (+,-) pozidriv 2</b>
<b>Marking Terminals</b>	<b>According to IEC 60947-5-1</b>
<b>Mechanical Durability [Millions of Operations]</b>	<b>1</b>
<b>B10d [Millions of Operations]</b>	<b>2</b>

**PRODUCT DRAWING RELEASE:**

Datasheet creation date: 23/01/2023 13:59

Last Modification (geometry): 14/08/2020 06:16

