

Index

A

Address
 assigning a hardware address, 15
 conventions, 20
 setting the dip switch, 15
Addressing conventions, 20

B

Bezel, 5
Bit-of-Word, 22

C

Cable requirements, 9
 cables, 10
 shielded cable, 12, 13
Communications Master, 9
Connector specification, 10
 Programming cable, 10
Connector specifications, 12, 13
 PLC-to-Panel cable, 10
Control relays, 24, 25, 27, 29
Cutout area for panel, 8

D

DCM, 12, 13
DCU, 12, 13
Dimensions for mounting, 8
DirectSOFT, 2

G

GE Series 1, 12, 13

I

Internal Relays, 22

L

Labels, 5
 Preparing labels, 5
 Template, 5
Legend, 5

M

Memory mapping, 17

N

NEMA, 7

O

Octal numbers, 24, 25
OP-9001, 9,16
OP-CMCON-1, 12, 13
OP-CMCON-2, 12, 13

P

Power supply, 14
Product support, 17, 18

R

Remapping, 22, 26
Ribbon cable, 9
RS422, 16

S

SIMATIC, 12, 13
SLC500, 12, 13
5/03, 12, 13
Slice I/O, 12, 13
Specifications, 7

T

Termination resistor, 15
TI305, 12, 13
TI405, 12, 13
