

Index

A

Address

- Assigning a hardware address, 15
- Conventions, 18
- Setting the dip switch, 15
- Termination resistor, 15

Addressing conventions, 24

Allen-Bradley (Cables for), 12

- Micrologix, 12
- SLC500, 12
 - 5/03, 12
 - 5/04, 12

B

Bezel, 6

Bit-of-Word, 19

C

Cable requirements, 10

- shielded cable, 13

Communications master, 10

Connector Specification, 11

- Programming Cable, 11
- PLC-to-Panel Cable, 11

Control relays, 25, 31

Cutout Area for Panel, 9

D

DCM, 13

DCU, 13

Decimal numbers, 25

Dimensions for Mounting, 9

DIP switch, 5

DirectSOFT, 2

F

Force Function, 23

G

GE Series 1, 12

I

Internal Relays, 19

L

Labels, 6

- Preparing labels, 6
- Template, 7

Legend, 6

M

Memory mapping, 3

N

NEMA, 5

O

Octal numbers, 25
OP-9001, 10, 16
OP-CMCON-1, 13
OP-CMCON-2, 13
OP-WINEDIT, 2

P

Power supply, 14

R

Remapping, 19, 30
Ribbon cable, 10
RS422, 16
Pinouts, 11

S

SIMATIC, 13
SLC500, 13
5/03, 13
Slice I/O, 13
Specifications, 8
Communication Link, 8
Diagnostics, 8
NEMA rating, 8
Operating Humidity, 8
Operating Temperature, 8
NEMA rating, 8
storage temperature, 8
operating humidity, 8
operating temperature, 8
power budget, 8
power connector, 8
weight, 8, 15

T

Termination resistor, 15
TI305, 13
TI405, 13
