



**Background suppression sensor - PNP**  
**LHR-C23PA-PMS-603**


**PROUDLY  
MADE IN USA**

For use in NFPA 79 Applications only **IO-Link**

Sensing range  
typ. max. **10...300 mm**

Housing **20 x 30 (C23)**

Operation range **15...250 mm**



$U_b$  10...30 VDC  
 $I_A \leq 100$  mA

A1: Light-on/IO-Link  
A2: Dark-on

For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.




**CONTRINEX USA**  
480 Wrangler Dr 100, Coppell TX 75019 US  
Internet: [www.contrinex.com](http://www.contrinex.com)



Made by Contrinex USA

620-400-340

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.



**Background suppression sensor - PNP**  
**LHR-C23PA-PMS-603**


**PROUDLY  
MADE IN USA**

For use in NFPA 79 Applications only **IO-Link**

Sensing range  
typ. max. **10...300 mm**

Housing **20 x 30 (C23)**

Operation range **15...250 mm**



$U_b$  10...30 VDC  
 $I_A \leq 100$  mA

A1: Light-on/IO-Link  
A2: Dark-on

For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.



**CONTRINEX USA**  
480 Wrangler Dr 100, Coppell TX 75019 US  
Internet: [www.contrinex.com](http://www.contrinex.com)



Made by Contrinex USA

620-400-340

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.



**Background suppression sensor - PNP**  
**LHR-C23PA-PMS-603**


**PROUDLY  
MADE IN USA**

For use in NFPA 79 Applications only **IO-Link**

Sensing range  
typ. max. **10...300 mm**

Housing **20 x 30 (C23)**

Operation range **15...250 mm**



$U_b$  10...30 VDC  
 $I_A \leq 100$  mA


A1: Light-on/IO-Link  
A2: Dark-on

For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.



**CONTRINEX USA**  
480 Wrangler Dr 100, Coppell TX 75019 US  
Internet: [www.contrinex.com](http://www.contrinex.com)



**Background suppression sensor - PNP**  
**LHR-C23PA-PMS-603**


**PROUDLY  
MADE IN USA**

For use in NFPA 79 Applications only **IO-Link**

Sensing range  
typ. max. **10...300 mm**

Housing **20 x 30 (C23)**

Operation range **15...250 mm**



$U_b$  10...30 VDC  
 $I_A \leq 100$  mA

A1: Light-on/IO-Link  
A2: Dark-on

For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.



**CONTRINEX USA**  
480 Wrangler Dr 100, Coppell TX 75019 US  
Internet: [www.contrinex.com](http://www.contrinex.com)