





Background suppression sensor - NPN LHR-M18PA-PMS-101

For use in NFPA 79 Applications only

Sensing range


typ. max.

10...250 mm

Housing M18

Operation range

15...210 mm



U_B 10...30 VDC IA ≤ 200 mA

A1: Light-on A2: Dark-on

For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.

WARNING - HOT SURFACE - RISK OF BURN

AVERTISSEMENT - SURFACE CHAUDE - RISQUE DE BRÛLURE



ECOLAB





CONTRINEX USA

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.







Background suppression sensor - NPN LHR-M18PA-PMS-101

For use in NFPA 79 Applications only

Sensing range


typ. max.

10...250 mm

Housing M18

Operation range

15...210 mm



U_n 10...30 VDC

 $IA \leq 200 \ mA$

A1: Light-on A2: Dark-on

For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer.

Refer to manufacturers information.

WARNING - HOT SURFACE - RISK OF BURN - AVERTISSEMENT - SURFACE CHAUDE - RISQUE DE BRÚLUBE







IND. CONT. EQ 11RZ

CONTRINEX USA 480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

620-400-206

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.

CONTRINE





Background suppression sensor - NPN **LHR-M18PA-PMS-101**

For use in NFPA 79 Applications only

Sensing range


typ. max.

10...250 mm

Housing M18

Operation range

15...210 mm



U_B 10...30 VDC

IA ≤ 200 mA

A1: Light-on A2: Dark-on

For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.

WARNING - HOT SURFACE - RISK OF BURN AVERTISSEMENT - SURFACE CHAUDE - RISQUE DE BRÛLURE







CONTRINEX USA

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

620-400-206 Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.







Background suppression sensor - NPN LHR-M18PA-PMS-101

For use in NFPA 79 Applications only


Sensing range typ. max.

10...250 mm

Housing M18

Operation range

15...210 mm



Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.

A2: Dark-on

WARNING - HOT SURFACE - RISK OF BURN - AVERTISSEMENT - SURFACE CHAUDE - RISQUE DE BRÛLURE







CONTRINEX USA

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

620-400-206

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.