


# CONTRINEX



## Through-beam sensor - PNP LLR-C23PA-NMK-603

**PROUDLY  
MADE IN USA**


For use in NFPA 79 Applications only



Sensing range  
typ. max. **0...30000 mm**

Housing **20 x 30 (C23)**

Operation range **0...25000 mm**



$U_b$  10...30 VDC  
 $I_A \leq 100$  mA

A1: Light-on/IO-Link  
A2: Dark-on

For use in class 2 circuits



**CONTRINEX USA**  
480 Wrangler Dr 100, Coppell TX 75019 US  
Internet: [www.contrinex.com](http://www.contrinex.com)




620-400-322

Made by Contrinex USA

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.

# CONTRINEX



## Through-beam sensor - PNP LLR-C23PA-NMK-603

**PROUDLY  
MADE IN USA**


For use in NFPA 79 Applications only



Sensing range  
typ. max. **0...30000 mm**

Housing **20 x 30 (C23)**

Operation range **0...25000 mm**



$U_b$  10...30 VDC  
 $I_A \leq 100$  mA

A1: Light-on/IO-Link  
A2: Dark-on

For use in class 2 circuits



**CONTRINEX USA**  
480 Wrangler Dr 100, Coppell TX 75019 US  
Internet: [www.contrinex.com](http://www.contrinex.com)




620-400-322

Made by Contrinex USA

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.

# CONTRINEX



## Through-beam sensor - PNP LLR-C23PA-NMK-603

**PROUDLY  
MADE IN USA**


For use in NFPA 79 Applications only



Sensing range  
typ. max. **0...30000 mm**

Housing **20 x 30 (C23)**

Operation range **0...25000 mm**



$U_b$  10...30 VDC  
 $I_A \leq 100$  mA


A1: Light-on/IO-Link  
A2: Dark-on

For use in class 2 circuits



**CONTRINEX USA**  
480 Wrangler Dr 100, Coppell TX 75019 US  
Internet: [www.contrinex.com](http://www.contrinex.com)

# CONTRINEX



## Through-beam sensor - PNP LLR-C23PA-NMK-603

**PROUDLY  
MADE IN USA**

For use in NFPA 79 Applications only



Sensing range  
typ. max. **0...30000 mm**

Housing **20 x 30 (C23)**

Operation range **0...25000 mm**



$U_b$  10...30 VDC  
 $I_A \leq 100$  mA

A1: Light-on/IO-Link  
A2: Dark-on

For use in class 2 circuits



**CONTRINEX USA**  
480 Wrangler Dr 100, Coppell TX 75019 US  
Internet: [www.contrinex.com](http://www.contrinex.com)