





Through-beam sensor - Emitter LLR-C23PA-NMS-400

PROUDLY

For use in NFPA 79 Applications only

**IO**-Link

Sensing range


typ. max.

0...30000 mm

Housing 20 x 30 (C23)

Operation range

0...25000 mm



U<sub>B</sub> 10...30 VDC IA ≤ 100 mA

For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.





## **CONTRINEX USA**

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

620-400-320

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.







PROUDLY

Through-beam sensor - Emitter LLR-C23PA-NMS-400

**IO**-Link

For use in NFPA 79 Applications only


Sensing range typ. max.

0...30000 mm

Housing 20 x 30 (C23)

Operation range

0...25000 mm







For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.





## **CONTRINEX USA**

IA ≤ 100 mA

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com

...... Mada la la Osalda a UlOA



Through-beam sensor - Emitter

LLR-C23PA-NMS-400





PROUDLY

For use in NFPA 79 Applications only

**IO**-Link

Sensing range


typ. max.

0...30000 mm

Housing 20 x 30 (C23)

Operation range

0...25000 mm



U<sub>B</sub> 10...30 VDC IA ≤ 100 mA

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.







**CONTRINEX USA** 

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

620-400-320

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.





**IO**-Link



Through-beam sensor - Emitter LLR-C23PA-NMS-400

For use in NFPA 79 Applications only

Sensing range

typ. max.


0...30000 mm

Housing 20 x 30 (C23)

IA ≤ 100 mA

Operation range

0...25000 mm



Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.







**CONTRINEX USA** 

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com