





# Through-beam sensor - NPN LLR-M18PA-NMS-101

For use in NFPA 79 Applications only

Sensing range


tvp. max.

0...30000 mm

Housing M18

Operation range

0...25000 mm



U<sub>s</sub> 10...30 VDC IA ≤ 200 mA

A1: Light-on

For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.

WARNING - HOT SURFACE - RISK OF BURN

AVERTISSEMENT - SURFACE CHAUDE - RISQUE DE BRÛLURE







### **CONTRINEX USA**

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.







# Through-beam sensor - NPN LLR-M18PA-NMS-101

For use in NFPA 79 Applications only

Sensing range

typ. max.

0...30000 mm

Housing M18

Operation range

0...25000 mm



Adapters providing field wiring means are available from the manufacturer.

Refer to manufacturers information

WARNING - HOT SURFACE - RISK OF BURN - AVERTISSEMENT - SURFACE CHAUDE - RISQUE DE BRÚLURE









## **CONTRINEX USA**

480 Wrangler Dr 100, Coppell TX 75019 US

11RZ

Internet: www.contrinex.com



Made by Contrinex USA

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.







# Through-beam sensor - NPN LLR-M18PA-NMS-101

For use in NFPA 79 Applications only


Sensing range tvp. max.

0...30000 mm

Housing M18

Operation range

0...25000 mm



U。 10...30 VDC

IA ≤ 200 mA

A2: Dark-on

For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.

WARNING - HOT SURFACE - RISK OF BURN - AVERTISSEMENT - SURFACE CHAUDE - RISQUE DE BRÛLURE







## **CONTRINEX USA**

480 Wrangler Dr 100, Coppell TX 75019 US

11R7

Internet: www.contrinex.com



Made by Contrinex USA

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines







# Through-beam sensor - NPN LLR-M18PA-NMS-101

For use in NFPA 79 Applications only


Sensing range tvp. max.

0...30000 mm

Housing M18

Operation range

0...25000 mm



 $IA \le 200 \text{ mA}$ Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.

WARNING - HOT SURFACE - RISK OF BURN - AVERTISSEMENT - SURFACE CHAUDE - RISQUE DE BRÛLURE



IND. CONT. EQ 11RZ

**ECOLAB** 







## **CONTRINEX USA**

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

620-400-231

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.