

Retro-reflective sensor - NPN

LRR-C23PA-NMS-101





PROUDLY

For use in NFPA 79 Applications only

Sensing range

typ. max.

20...8000 mm


Housing 20 x 30 (C23)

(on LXR-0000-084)

Operation range

30...6000 mm

(on LXR-0000-084)





A1: Light-on A2: Dark-on For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.







**CONTRINEX USA** 480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

620-400-317

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.







Retro-reflective sensor - NPN LRR-C23PA-NMS-101

For use in NFPA 79 Applications only

Sensing range typ. max.

20...8000 mm

Housing 20 x 30 (C23)

(on LXR-0000-084)

Operation range 30...6000 mm

A2

(on LXR-0000-084)

bk A1







U<sub>n</sub> 10...30 VDC A1: Light-on A2: Dark-on IA ≤ 100 mA

For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.









480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com 

Made by Contrincy LICA



LRR-C23PA-NMS-101



## Retro-reflective sensor - NPN

For use in NFPA 79 Applications only

Sensing range

typ. max.


20...8000 mm

(on LXR-0000-084) Housing 20 x 30 (C23)

Operation range

30...6000 mm

(on LXR-0000-084)





A1: Light-on

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.









**CONTRINEX USA** 

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

620-400-317

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.







Retro-reflective sensor - NPN LRR-C23PA-NMS-101

For use in NFPA 79 Applications only

Housing 20 x 30 (C23)

Sensing range

typ. max.


20...8000 mm (on LXR-0000-084)


Operation range

30...6000 mm

(on LXR-0000-084)

+Ub







Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.



 $IA \le 100 mA$ 







**CONTRINEX USA** 

Internet: www.contrinex.com

480 Wrangler Dr 100, Coppell TX 75019 US

Made by Contrinov IICA