





Retro-reflective sensor - PNP

LRR-C23PA-NMS-603

PROUDLY

For use in NFPA 79 Applications only

Housing 20 x 30 (C23)

IO-Link

Sensing range


20...8000 mm typ. max.

(on LXR-0000-084)

Operation range

30...6000 mm

(on LXR-0000-084)



U_B 10...30 VDC IA ≤ 100 mA

A1: Light-on/IO-Link

For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.







11RZ

CONTRINEX USA 480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

620-400-314

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.







Retro-reflective sensor - PNP LRR-C23PA-NMS-603

For use in NFPA 79 Applications only

IO-Link

Sensing range typ. max.

20...8000 mm


Housing 20 x 30 (C23)

(on LXR-0000-084)

Operation range

30...6000 mm

(on LXR-0000-084)



U_B 10...30 VDC IA ≤ 100 mA

A1: Light-on/IO-Link A2: Dark-on

For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.









480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com

CONTRINEX USA

Made by Centriney LICA



Retro-reflective sensor - PNP

LRR-C23PA-NMS-603





20...8000 mm

For use in NFPA 79 Applications only

Housing 20 x 30 (C23)

IO-Link

Sensing range

typ. max.

(on LXR-0000-084)

Operation range

30...6000 mm

(on LXR-0000-084)

bk A1 wh A2 bu ov

U_B 10...30 VDC IA ≤ 100 mA

A1: Light-on/IO-Link

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.









CONTRINEX USA

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

620-400-314

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines







Retro-reflective sensor - PNP

LRR-C23PA-NMS-603

bk

wh

bu

For use in NFPA 79 Applications only

IO-Link

Sensing range 20...8000 mm typ. max.

(on LXR-0000-084) Housing 20 x 30 (C23)

Operation range 30...6000 mm

(on LXR-0000-084)

+Ub A1 A2



U_B 10...30 VDC IA ≤ 100 mA

A1: Light-on/IO-Link A2: Dark-on

For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.







CONTRINEX USA

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com

Made by Contriney LICA