





# Retro-reflective sensor - NPN LRR-M18PA-NMS-101

For use in NFPA 79 Applications only

Sensing range

typ. max.


20...7000 mm

Housing M18

(on LXR-0000-084) Operation range

30...5500 mm

(on LXR-0000-084)



A1: Light-on A2: Dark-on

Adapters providing field wiring means are available from the manufacturer.

Refer to manufacturers information.

WARNING - HOT SURFACE - RISK OF BURN - AVERTISSEMENT - SURFACE CHAUDE - RISQUE DE BRÛLURE







### **CONTRINEX USA**

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

620-400-244

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.







## **Retro-reflective sensor - NPN** LRR-M18PA-NMS-101

For use in NFPA 79 Applications only

Sensing range typ. max.

20...7000 mm


Housing M18

(on LXR-0000-084)

Operation range

30...5500 mm

(on LXR-0000-084)



U<sub>B</sub> 10...30 VDC  $IA \le 200 \ mA$ 

A2: Dark-on



For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.

WARNING - HOT SURFACE - RISK OF BURN - AVERTISSEMENT - SURFACE CHAUDE - RISQUE DE BRÛLURE







### **CONTRINEX USA**

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.







## Retro-reflective sensor - NPN LRR-M18PA-NMS-101

For use in NFPA 79 Applications only

Sensing range typ. max.


20...7000 mm

(on LXR-0000-084) Housing M18

Operation range

30...5500 mm

(on LXR-0000-084)



U<sub>B</sub> 10...30 VDC ≤ 200 mA

A2: Dark-on

A1: Light-on

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.

WARNING - HOT SURFACE - RISK OF BURN - AVERTISSEMENT - SURFACE CHAUDE - RISQUE DE BRÛLURE







#### **CONTRINEX USA**

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

620-400-244

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at fisk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.







# Retro-reflective sensor - NPN LRR-M18PA-NMS-101

For use in NFPA 79 Applications only

Sensing range typ. max.

20...7000 mm

Housing M18

(on LXR-0000-084)

Operation range

30...5500 mm

(on LXR-0000-084)



U<sub>B</sub> 10...30 VDC IA ≤ 200 mA

A1: Light-on A2: Dark-on

For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer Refer to manufacturers information.

WARNING - HOT SURFACE - RISK OF BURN - AVERTISSEMENT - SURFACE CHAUDE - RISQUE DE BRÛLURE







### **CONTRINEX USA**

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.