





Retro-reflective sensor - PNP LRR-M18PA-NMS-603

O-Link

For use in NFPA 79 Applications only

Sensing range

20...7000 mm typ. max.

Housing M18


IA < 200 mA

(on LXR-0000-084)

Operation range

30...5500 mm

(on LXR-0000-084)



For use in class 2 circuits A1: Light-on/IO-Link A2: Dark-on

Adapters providing field wiring means are available from the manufacturer

Refer to manufacturers information.

WARNING - HOT SURFACE - RISK OF BURN

AVERTISSEMENT - SURFACE CHAUDE - RISQUE DE BRÛLURE









480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.







Retro-reflective sensor - PNP LRR-M18PA-NMS-603

🚷 IO-Link

For use in NFPA 79 Applications only

Sensing range

typ. max.

20...7000 mm

Housing M18

(on LXR-0000-084)

Operation range

30...5500 mm

(on LXR-0000-084)

bn bk wh

bu

U_p 10...30 VDC IA ≤ 200 mA

3

A1: Light-on/IO-Link

+Ub A1 A2 OV



For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.

A2: Dark-on

WARNING - HOT SURFACE - RISK OF BURN - AVERTISSEMENT - SURFACE CHAUDE - RISQUE DE BRÛLURE







CONTRINEX USA

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.







Retro-reflective sensor - PNP LRR-M18PA-NMS-603

O IO-Link

For use in NFPA 79 Applications only

Sensing range typ. max.

20...7000 mm

Housing M18

(on LXR-0000-084)

Operation range


30...5500 mm

(on LXR-0000-084)



U_B 10...30 VDC 200 mA

A1: Light-on/IO-Link A2: Dark-on



Refer to manufacturers information.

WARNING - HOT SURFACE - BISK OF BURN -AVERTISSEMENT - SURFACE CHAUDE - RISQUE DE BRÛLURE









CONTRINEX USA

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

620-400-248

erators of the products we supply are responsible for compliance with measures for the protection of persons. The of our equipment in applications where the safety of persons might be at risk is only authorized if the operator erves and implements separate, appropriate and necessary measures for the protection of persons and machines.







Retro-reflective sensor - PNP LRR-M18PA-NMS-603

🚷 IO-Link

For use in NFPA 79 Applications only

Sensing range typ. max.


20...7000 mm

(on LXR-0000-084) Housing M18

Operation range

30...5500 mm

(on LXR-0000-084)







For use in class 2 circuits

A2: Dark-on Adapters providing field wiring means are available from the manufacturer Refer to manufacturers information.

WARNING - HOT SURFACE - RISK OF BURN - AVERTISSEMENT - SURFACE CHAUDE - RISQUE DE BRÛLURE



IA ≤ 200 mA



CONTRINEX USA

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.