





Diffuse sensor - PNP LTR-M18PA-PMS-603

O IO-Link

For use in NFPA 79 Applications only

Sensing range


typ. max.

3...1200 mm

Housing M18

Operation range

5...1000 mm



Adapters providing field wiring means are available from the manufacturer.

Refer to manufacturers information.

AVERTISSEMENT - SURFACE CHAUDE - BISQUE DE BRÛLURE WARNING - HOT SUBFACE - BISK OF BURN







CONTRINEX USA

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

620-400-262

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.







Diffuse sensor - PNP LTR-M18PA-PMS-603

IO-Link

For use in NFPA 79 Applications only

Sensing range

tvp. max.

3...1200 mm

Housing M18

Operation range


5...1000 mm



U_B 10...30 VDC

IA ≤ 200 mA









For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.

WARNING - HOT SURFACE - RISK OF BURN - AVERTISSEMENT - SURFACE CHAUDE - RISQUE DE BRÛLURE







CONTRINEX USA

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.







Diffuse sensor - PNP LTR-M18PA-PMS-603

O-Link

For use in NFPA 79 Applications only


Sensing range typ. max.

3...1200 mm

Housing M18

Operation range

5...1000 mm



U_B 10...30 VDC ≤ 200 mA

A1: Light-on/IO-Link A2: Dark-on

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.

WARNING - HOT SURFACE - RISK OF BURN - AVERTISSEMENT - SURFACE CHAUDE - RISQUE DE BRÛLURE







CONTRINEX USA

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.





+Ub

Α1

A2

OV



Diffuse sensor - PNP LTR-M18PA-PMS-603

IO-Link

For use in NFPA 79 Applications only


Sensing range typ. max.

3...1200 mm

Housing M18

Operation range

5...1000 mm



U_B 10...30 VDC IA ≤ 200 mA

A1: Light-on/IO-Link A2: Dark-on

For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.

WARNING - HOT SURFACE - RISK OF BURN - AVERTISSEMENT - SURFACE CHAUDE - RISQUE DE BRÛLURE







CONTRINEX USA

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operation observes and miplements separate, appropriate and necessary measures for the protection of persons and machines.