





Transparent object sensor - NPN TRR-C23PA-TMS-101

PROUDLY

For use in NFPA 79 Applications only

Sensing range

typ. max.

10...5000 mm

Housing 20 x 30 (C23)

(on LXR-0000-084)

Operation range

20...4200 mm

(on LXR-0000-084)

bk A1 A2 bu 0V



U_B 10...30 VDC IA ≤ 100 mA

A1: Light-on A2: Dark-on For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.





CONTRINEX USA

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

620-400-374

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.







Transparent object sensor - NPN TRR-C23PA-TMS-101

For use in NFPA 79 Applications only

Sensing range

typ. max.

10...5000 mm

Housing 20 x 30 (C23)

(on LXR-0000-084)

Operation range

20...4200 mm

(on LXR-0000-084)





U., 10...30 VDC IA ≤ 100 mA

A1: Light-on A2: Dark-on For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.











480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com

Made by Contrincy IICA





Transparent object sensor - NPN TRR-C23PA-TMS-101



For use in NFPA 79 Applications only

Housing 20 x 30 (C23)

Sensing range

typ. max.


10...5000 mm

(on LXR-0000-084)

Operation range

20...4200 mm

(on LXR-0000-084)



Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.

A1: Light-on



IA ≤ 100 mA







CONTRINEX USA

480 Wrangler Dr 100, Coppell TX 75019 US

11RZ

Internet: www.contrinex.com



Made by Contrinex USA

620-400-374

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.







Transparent object sensor - NPN TRR-C23PA-TMS-101

For use in NFPA 79 Applications only

Housing 20 x 30 (C23)

Sensing range


typ. max.

10...5000 mm (on LXR-0000-084)

Operation range

20...4200 mm

(on LXR-0000-084)





U_B 10...30 VDC IA ≤ 100 mA

A1: Light-on

For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.







CONTRINEX USA

Internet: www.contrinex.com

480 Wrangler Dr 100, Coppell TX 75019 US

Made by Contriney IICA