





Transparent object sensor - PNP TRU-C23PA-TMS-603

For use in NFPA 79 Applications only

O IO-Link

Sensing range

typ. max.

0...1200 mm


Housing 20 x 30 (C23)

(on LXU-0000-084)

Operation range

0...1000 mm

(on LXU-0000-084)



U_B 15...30 VDC A1: Light-on/IO-Link

For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.

A2: Dark-on



IA ≤ 100 mA







CONTRINEX USA

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

620-400-388

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.







Transparent object sensor - PNP

TRU-C23PA-TMS-603

For use in NFPA 79 Applications only

IO-Link

Sensing range typ. max.

0...1200 mm

Housing 20 x 30 (C23)

(on LXU-0000-084)

Operation range

0...1000 mm

(on LXU-0000-084)

bn bk A1 A2 bu 0V

U_B 15...30 VDC

IA ≤ 100 mA

A1: Light-on/IO-Link



For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.



ND. CONT. EQ 11RZ





480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com







Transparent object sensor - PNP TRU-C23PA-TMS-603

For use in NFPA 79 Applications only

Housing 20 x 30 (C23)

IO-Link

Sensing range

typ. max.


(on LXU-0000-084)

Operation range

0...1000 mm

0...1200 mm

(on LXU-0000-084)



U_B 15...30 VDC IA ≤ 100 mA

A1: Light-on/IO-Link

For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information





11RZ







CONTRINEX USA

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com



Made by Contrinex USA

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines.







Transparent object sensor - PNP TRU-C23PA-TMS-603

IO-Link



For use in NFPA 79 Applications only

Housing 20 x 30 (C23)

Sensing range

0...1200 mm typ. max. (on LXU-0000-084)

Operation range

(on LXU-0000-084)

0...1000 mm

bn +Ub bk A1 wh A2 ov



bu A1: Light-on/IO-Link



A2: Dark-on

For use in class 2 circuits

Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.











CONTRINEX USA

480 Wrangler Dr 100, Coppell TX 75019 US

Internet: www.contrinex.com