



Photoelectric Through-beam Fork Sensors U-Frame

Overview

The di-soric OGU series is ideal for applications requiring quick detection of small objects with any surface type and are available with fork openings from 5 to 250mm [0.19 to 9.84 in]. The OGU series fork sensors offer high-resolution, sensitivity adjustment and selectable Light-on/Dark-on operation. Four selectable modes optimize the sensors for standard, high-resolution, power, or speed operation using I/O Link v1.1, standard mode is default.

Features

- Light-on/Dark-on Selectable
- Up to 14 kHz switching frequency
- 10-30 VDC operating voltage
- IP67 protection rating
- Sensitivity adjustment via potentiometer or IO-Link v1.1
- Standard, high-resolution, power, and speed modes configured via I/O Link v1.1



OGU041G3-T3

Photoelectric Through-beam Fork Sensors - U Frame

Part Number	Price	Light Emission	Max. Switching Frequency	Fork Opening	Housing Material	Housing Size	Weight lb [g]	Drawing Link
OGU005G3-T3	\$0681q:	Infrared	14 kHz	5mm [0.19 in]	Aluminum	25 x 45 x 10mm [0.98 x 1.77 x 0.39 in]	0.07 [31.75]	PDF
OGU010G3-T3	\$0681s:		14 kHz	10mm [0.39 in]	Die-cast zinc	40 x 50 x 10mm [1.57 x 1.96 x 0.39 in]	0.06 [27.21]	PDF
OGU020G3-T3	\$0681t:		8 kHz	20mm [0.78 in]			0.11 [49.89]	PDF
OGU021G3-T3	\$0681u:	Visible red	8 kHz	50 x 60 x 10mm [1.57 x 2.36 x 0.39 in]		0.15 [68.03]		PDF
OGU030G3-T3	\$0681v:	Infrared	8 kHz			30mm [1.18 in]	60 x 70 x 10mm [2.36 x 2.75 x 0.39 in]	0.19 [86.18]
OGU031G3-T3	\$0681x:	Visible red	8 kHz	40mm [1.57 in]		70 x 80 x 10mm [2.75 x 3.14 x 0.39 in]		0.21 [95.25]
OGU041G3-T3	\$0681#:		8 kHz	50mm [1.96 in]		80 x 80 x 10mm [3.14 x 3.14 x 0.39 in]	0.22 [99.79]	PDF
OGU050G3-T3	\$0681!:	Infrared	8 kHz	60mm [2.36 in]	Aluminum	90 x 80 x 10mm [3.54 x 3.14 x 0.39 in]	0.13 [58.96]	PDF
OGU051G3-T3	\$06823:	Visible red	8 kHz			100 x 80 x 10mm [3.93 x 3.14 x 0.39 in]	0.15 [68.03]	PDF
OGU061G3-T3	\$06824:		8 kHz	70mm [2.75 in]	Die-cast zinc	100 x 80 x 10mm [3.93 x 3.14 x 0.39 in]	0.26 [117.93]	PDF
OGU071G3-T3	\$0681y:	Infrared	8 kHz	80mm [3.14 in]		100 x 105 x 10mm [3.93 x 4.13 x 0.39 in]	0.28 [127.00]	PDF
OGU080G3-T3	\$0681z:	Visible red	8 kHz	80mm [3.14 in]	Aluminum	110 x 80 x 10mm [4.33 x 3.14 x 0.39 in]	0.17 [77.11]	PDF
OGU081/80G3-T3	\$0681j:		8 kHz		90mm [3.54 in]	Aluminum	120 x 80 x 10mm [4.72 x 3.14 x 0.39 in]	0.29 [131.54]
OGU081G3-T3	\$0681[:		8 kHz	100mm [3.93 in]	Die-cast zinc	144 x 90 x 12mm [5.66 x 3.54 x 0.47 in]	0.69 [312.97]	PDF
OGU091G3-T3	\$0681_:		Infrared	8 kHz		120mm [4.72 in]		144 x 175 x 12mm [5.66 x 6.88 x 0.47 in]
OGU101G3-T3	\$0681?:	Visible red	8 kHz	120mm [4.72 in]	Aluminum	144 x 235 x 12mm [5.66 x 9.25 x 0.47 in]	0.74 [335.65]	PDF
OGU120G3-T3	\$0681,::		8 kHz			144 x 90 x 12mm [5.66 x 3.54 x 0.47 in]	0.66 [299.37]	PDF
OGU121/145G3-T3	\$06820:		8 kHz	170mm [6.69 in]	Die-cast zinc	194 x 140 x 12mm [7.63 x 5.51 x 0.47 in]	1.07 [485.34]	PDF
OGU121/205G3-T3	\$06821:		8 kHz			244 x 140 x 12mm [9.60 x 5.51 x 0.47 in]	1.21 [548.84]	PDF
OGU121G3-T3	\$06822:		8 kHz	250mm [9.84 in]	Aluminum	274 x 140 x 12mm [10.78 x 5.51 x 0.47 in]	0.77 [349.26]	PDF
OGU171G3-T3	\$06825:		Class 1 red laser	10 kHz	30mm [1.18 in]	Die-cast zinc	50 x 60 x 10mm [1.57 x 2.36 x 0.39 in]	0.15 [68.03]
OGU221G3-T3	\$06826:	6.5 kHz		220mm [8.66 in]	70 x 80 x 10mm [2.75 x 3.14 x 0.39 in]		0.19 [86.18]	PDF
OGU251G3-T3	\$06827:	6.5 kHz		80mm [3.14 in]	100 x 80 x 10mm [3.93 x 3.14 x 0.39 in]		0.26 [117.93]	PDF
OGUL031G3-T3	\$06828:	10 kHz		120mm [4.72 in]	144 x 90 x 12mm [5.66 x 3.54 x 0.47 in]		0.66 [299.37]	PDF
OGUL051G3-T3	\$06829:	10 kHz						
OGUL081G3-T3	\$0682a:	10 kHz						
OGUL121G3-T3	\$0682b:	10 kHz						



Photoelectric Through-beam Fork Sensors U-Frame



Photoelectric Through-beam Fork Sensors - U Frame Specifications	
Operating Voltage	10–30 VDC
Maximum No-load Current	30mA
Insulation Voltage Endurance	500V
Protection Class	III, operation on protective low voltage
Operation Modes	Standard, high resolution, power, speed
Interface	IO-Link (V1.1, COM2 38.4 kBd, Smart Sensor Profile)
Light Source	LED
Output State	Light-On / Dark-On (selectable)
Switching Output	Push-pull, NPN or PNP, 100mA
Operating Temperature	-25 to 60°C [-13 to 140°F]
Connection	3-pin M8 quick-disconnect (purchase cable separately)
Protection Type	IP67
Agency Approval	cULus File E303138, CE, UKCA

To obtain the most current agency approval information, see the Agency Compliance & Certifications Checklist section on the specific part number's web page.

Wiring Diagram

