## 1351E-6504 Cut Sheet





Eaton photoelectric sensor, rectangular, diffuse, infrared, 10ft sensing distance, selectable light-on/dark-on, SPDT EM relay, potentiometer, 66 Hz switching frequency, plastic housing, 5-pin mini connector and 7/8in - 16UNF thread.

For complete product information, please see this item on our store at the following link:



https://www.automationdirect.com/pn/1351E-6504

## **Technical Specifications**

Eaton	Switching Output	SPDT EM relay
Photoelectric sensor	Sensing Distance	10ft
Rectangular	Sensitivity	Potentiometer
73 x 48.5 x 46mm	Operation Mode	Selectable light-on/dark-on
30mm	Switching Frequency	66 Hz
IP67 IP69K	Light Emission (NP)	Infrared
Plastic	IO-Link Compatible	No
Diffuse	Connection	5-pin mini connector and 7/8in - 16UNF thread
12-240 VDC/24-240 VAC	Includes	Mounting hardware
5	Additional Information	Purchase cable separately
	Photoelectric sensor Rectangular 73 x 48.5 x 46mm 30mm IP67 IP69K Plastic Diffuse 12-240 VDC/24-240 VAC	Photoelectric sensorSensing DistanceRectangularSensitivity73 x 48.5 x 46mmOperation Mode30mmSwitching FrequencyIP67 IP69KLight Emission (NP)PlasticIO-Link CompatibleDiffuseConnection12-240 VDC/24-240 VACIncludes

## Agency Approvals

UL Listed File #	None
UL Recognized File #	None
UL Hazardous File #	None
CE	View CE declarations
RoHS Status	Yes (See CE Doc)
EU REACH	View EU REACH document