



Eaton photoelectric sensor, rectangular, polarized retroreflective, visible red light emission, 16ft sensing distance, selectable light-on/dark-on, solid state relay, potentiometer, 4-wire, 4-pin mini connector and 7/8in - 16UNF thread.

For complete product information, please see this item on our store at the following link:



https://www.automationdirect.com/pn/1451E-6503

Technical Specifications

| Brand | Eaton |
|---------------------------|---------------------------|
| Item | Photoelectric sensor |
| Shape | Rectangular |
| Housing Size | 73 x 48.5 x 46mm |
| Thread mounting base size | 30mm |
| IP Rating | IP67 |
| Housing Material | Plastic |
| Sensing Method | Polarized retroreflective |
| Operating Voltage | 12-240 VDC/24-240 VAC |
| Number of Wires | 4 |

| Switching Output | Solid state relay |
|------------------------|---|
| Sensing Distance | 16ft |
| Sensitivity | Potentiometer |
| Operation Mode | Selectable light-on/dark-on |
| Switching Frequency | 500 Hz |
| Light Emission | Visible red |
| Connection | 4-pin mini connector and 7/8in - 16UNF thread |
| Includes | Mounting hardware |
| Additional Information | Purchase cable separately |

Agency Approvals

| UL Listed File # | None |
|----------------------|------------------------|
| UL Recognized File # | None |
| UL Hazardous File # | None |
| CE | View CE declarations |
| RoHS Status | Yes (See CE Doc) |
| EU REACH | View EU REACH document |