## 6200-650-AAC3C-A Cut Sheet





Spartan solenoid valve, 2-way, 2-position, N.C., glass-filled nylon body, 3/8in female NPT inlet(s), 3/8in female NPT outlet(s), Cv=0.31, 150 psi maximum operating pressure, 24 VDC operating voltage, 18mm DIN style wiring plug.

For complete product information, please see this item on our store at the following link:



https://www.automationdirect.com/pn/6200-650-AAC3C-A

## **Technical Specifications**

Spartan
6200
Valve
Potable water
Solenoid process
2-way
2
N.C.
Direct acting
Single solenoid spring return
Glass-filled nylon

IP Rating	IP65
Inlet Port	3/8in female NPT
Outlet Port	3/8in female NPT
Flow Coefficient	0.31
Maximum Operating Pressure	150 psi
Minimum Operating Pressure	Vacuum
Operating Voltage	24 VDC
<b>Electrical Connection</b>	18mm DIN style wiring plug

## Agency Approvals

UL Listed File #	None
UL Recognized File #	None
UL Hazardous File #	None
CSA File #	None
RoHS Status	Yes (See CE Doc)
EU REACH	View EU REACH document

## **Dimensional Drawings**



2D Drawing PDF Link: https://cdn.automationdirect.com /static/drawings/2d/6200-650-AAC3C-A.pdf See store item page for other formats.