

# A6012003-1 Cut Sheet



LUTZE Silflex FBP flexible control cable, unshielded, 3 conductors (includes ground), 20 AWG, bare copper, polypropylene conductor insulation material, black with white numbers and green/yellow ground, TPE jacket, black, cut to length.

For complete product information, please see this item on our store at the following link:



<https://www.automationdirect.com/pn/A6012003-1>

## Technical Specifications

<b>Brand</b>	LUTZE	<b>Conductor Insulation Color</b>	Black with white numbers and green/yellow ground
<b>Item</b>	Cable	<b>Shielding</b>	Unshielded
<b>Series</b>	Silflex FBP	<b>Jacket Material</b>	TPE
<b>Wire/Cable Type</b>	Control	<b>Jacket Color</b>	Black
<b>UL Wire/Cable Type</b>	AWM	<b>Nominal Overall Cable Diameter</b>	0.203in
<b>Applicable Standards</b>	UL 20886	<b>Bulk Length</b>	Cut to length
<b>Application</b>	Food and beverage	<b>Package Type</b>	1 to 99ft = Coil, 100 to 945ft = 14 x 7in Reel, 946 to 1350ft = 14 x 10in Reel, 1351 to 2075ft = 16 x 10in Reel, 2076 to 2895ft = 18 x 10in Reel, 2896 to 3765ft = 18 x 13in Reel, 3766 to 8425ft = 24 x 17in Wooden Reel, 8426 to 13480ft = 30 x 17in Wooden Reel, 13481 to MAX = Large Wooden Reel
<b>Flexibility</b>	Flexible		
<b>Voltage Rating</b>	1000V		
<b>Conductors</b>	3 conductors (includes ground)		
<b>Conductor Size</b>	20 AWG		
<b>Conductor Stranding</b>	10-stranded		
<b>Conductor Material</b>	Bare copper		
<b>Conductor Insulation Material</b>	Polypropylene		

## Agency Approvals

<b>UL Listed File #</b>	None
<b>UL Recognized File #</b>	E197090
<b>UL Hazardous File #</b>	None
<b>CSA File #</b>	None
<b>RoHS Status</b>	Meets RoHS Chemical Restrictions - No CE (See RoHS Statement Below)
<b>EU REACH</b>	<a href="#">View EU REACH document</a>
<b>Other</b>	<a href="#">RoHS Statement</a>