## AM1-AP-1H Cut Sheet





Micro Detectors inductive proximity sensor, tubular, 12mm diameter x 65mm body, nickel-plated brass housing, PNP, N.O. output, 2mm sensing distance, flush, 2 kHz switching frequency, IP67, 4-pin M12 quick-disconnect.

For complete product information, please see this item on our store at the following link:



https://www.automationdirect.com/pn/AM1-AP-1H

	$\sim$		
Inchnical	$\subseteq$ n $\cap$	へけいへつ	ntiana
<b>Technical</b>		$\cup$ 111 $\cup$ 0	วนบบเธ

recrimed opening	Jations	
Brand	Micro Detectors	
Item	Proximity sensor	
Sensor Type	Inductive	
Application	Standard duty	
Shape	Tubular	
Housing Size	12mm diameter x 65mm body	
Housing Material	Nickel-plated brass	
Barrel Type	Threaded	
Sensing Method	Standard sensing	
Adjustable	No	
Number of Wires	3	
Switching Output	PNP	
Operation Mode	N.O. output	
Sensing Distance	2mm	
Mounting Type	Flush	
IO-Link Compatible	No	
<b>Switching Frequency</b>	2 kHz	
Operating Voltage	10-30 VDC	
<b>Operating Temperature</b>	-25 to 70c	
Weld Field Immune	No	
Chip Immune	No	
IP Rating	IP67	
Connection	4-pin M12 quick-disconnect	
Includes	Mounting hardware	
Additional Information	Purchase cable separately	

## Agency Approvals

UL Listed File #	Not Applicable	
UL Recognized File #	E130644	
UL Hazardous File #	Not Applicable	
CE	View CE declarations	
RoHS Status	Yes (See CE Doc)	
EU REACH	Vew EU REACH document	
Other	None	