APMC-FBL04AYK-AD Cut Sheet





LS Electric low inertia AC brushless servo motor, 400W, 3-phase input, 17-bit (131072 ppr) encoder. For use with LS Electric L7C L7CA004U-AD 400W drive.

For complete product information, please see this item on our store at the following link:



https://www.automationdirect.com/pn/APMC-FBL04AYK-AD

Technical Specifications

LS Electric
Servo motor
Low inertia
AC
Brushless
400W
3
3000rpm
5000rpm
2.6A
11.2 lb-in

Encoder Resolution	17-bit (131072 ppr)
Integrated Brake	No
Motor Frame	60mm
IP Rating	IP67
Shaft Type	Single
Shaft Diameter	14mm
Steps per Revolution	Up to 17-bit (131072 ppr)
For Use With	LS Electric L7C L7CA004U-AD 400W drive
Includes	Motor shaft key
Requires	LS Electric APCS-PxxxxLSC-AD power cables and APCS-ExxxxES-AD encoder cables

Agency Approvals

UL Listed File #	None
UL Recognized File #	E255738
UL Hazardous File #	None
CE	View CE declarations
CSA File #	None
RoHS Status	Yes (See CE Doc)
EU REACH	View EU REACH document
Other	RoHS Statement

Dimensional Drawings



2D Drawing PDF Link: https://cdn.automationdirect.com /static/drawings/APMC-FBL04AYK-AD.pdf See store item page for other formats.