BNI008M Cut Sheet





Balluff EtherNet/IP IO-Link master, (8) IO-Link capable I/O points, up to (16) discrete I/O points, IO-Link v1.1.3, 9A, 2A/port, plastic housing, IP67, -5 to 70 deg C, multi-line LCD display.

For complete product information, please see this item on our store at the following link:



https://www.automationdirect.com/pn/BNI008M

Technical Specifications

reenned speemeddons	
Brand	Balluff
Item	IO-Link master
Number of IO-Link Capable I/O Points	8
Number of Discrete I/O Points	Up to (16)
Discrete I/O Port Type(s)	(8) 5-pin M12 A-coded
Nominal Input Voltage	24 VDC
Discrete Input Type	Sinking
Number of Non-Isolated Discrete Input Commons	1
Number of Points per Discrete Input Common	16
Nominal Output Voltage	24 VDC
Discrete Output Type	Sourcing
Number of Non-Isolated Discrete Output Commons	1
Number of Points per Discrete Output Common	16
Communication Port and Connection Type(s)	 (2) 4-pin M12 D-coded (8) 5-pin M12 A-coded (IO-Link)
Port Protocol(s)	 EtherNet/IP MQTT Client webserver (secure HTTPs) IO-Link Class A Master

• IO-Link COM2 • IO-Link COM3 • IO-Link Version IO-Link v1.1.3 ne Side Port(s) (1) 7/8in - 16 UN2 thread nut 4-pin male axial bad Side Port(s) (1) 7/8in - 16 UN2 thread nut 4-pin female axial bad Side Port(s) (1) 7/8in - 16 UN2 thread nut 4-pin female axial bad Side Port(s) (1) 7/8in - 16 UN2 thread nut 4-pin female axial bad Current 2A/port isplay Type Multi-line LCD display dicator LED ousing Material		
ne Side Port(s)(1) 7/8in - 16 UN2 thread nut 4-pin male axiaload Side Port(s)(1) 7/8in - 16 UN2 thread nut 4-pin female axiaload Side Port(s)(24 VDCmperage Rating9Aoad Current2A/portisplay TypeMulti-line LCD displaydicatorLEDousing MaterialPlastic	Port Speed(s)	• IO-Link COM1 • IO-Link COM2
bad Side Port(s) (1) 7/8in - 16 UN2 thread nut 4-pin female axial kternal Power Requirement 24 VDC mperage Rating 9A bad Current 2A/port isplay Type Multi-line LCD display dicator LED ousing Material Plastic	IO-Link Version	IO-Link v1.1.3
Atternal Power Requirement 24 VDC mperage Rating 9A bad Current 2A/port isplay Type Multi-line LCD display idicator LED ousing Material Plastic	Line Side Port(s)	(1) 7/8in - 16 UN2 thread nut 4-pin male axial
mperage Rating 9A pad Current 2A/port isplay Type Multi-line LCD display dicator LED ousing Material Plastic	Load Side Port(s)	(1) 7/8in - 16 UN2 thread nut 4-pin female axial
bad Current 2A/port isplay Type Multi-line LCD display dicator LED ousing Material Plastic	External Power Requirement	24 VDC
isplay Type Multi-line LCD display dicator LED ousing Material Plastic	Amperage Rating	9A
dicator LED ousing Material Plastic	Load Current	2A/port
ousing Material Plastic	Display Type	Multi-line LCD display
	Indicator	LED
	Housing Material	Plastic
Prating IP67	IP Rating	IP67
emperature Rating -5 to 70 deg C	Temperature Rating	-5 to 70 deg C
cludes Marking tags	Includes	Marking tags
rogramming Software None, configure via Internet browser	Programming Software	None, configure via Internet browser

Agency Approvals

UL Listed File #	E319845
UL Recognized File #	None
UL Hazardous File #	None
CE	View CE declarations
CSA File #	None
RoHS Status	Yes (See CE Doc)
EU REACH	View EU REACH document

Dimensional Drawings



2D Drawing PDF Link: https://cdn.automationdirect.com /static/drawings/2d/BNI008M.pdf See store item page for other formats.