

BNI00HM Cut Sheet



Balluff EtherNet/IP IO-Link master, (8) IO-Link capable I/O points, up to (16) discrete I/O points, IO-Link v1.1.3, 9A, 2A/port, die-cast zinc nickel-plated housing, IP67, -25 to 70 deg C.

For complete product information, please see this item on our store at the following link:



<https://www.automationdirect.com/pn/BNI00HM>

Technical Specifications

Brand	Balluff
Item	IO-Link master
Number of IO-Link Capable I/O Points	8
Number of Discrete I/O Points	Up to (16)
Discrete I/O Port Type(s)	(8) 5-pin M12 A-coded
Nominal Input Voltage	24 VDC
Discrete Input Type	Sinking
Number of Non-Isolated Discrete Input Commons	1
Number of Points per Discrete Input Common	16
Nominal Output Voltage	24 VDC
Discrete Output Type	Sourcing
Number of Non-Isolated Discrete Output Commons	1
Number of Points per Discrete Output Common	16
Communication Port and Connection Type(s)	<ul style="list-style-type: none">• (2) 4-pin M12 D-coded• (8) 5-pin M12 A-coded (IO-Link)

Port Protocol(s)	<ul style="list-style-type: none">• EtherNet/IP• MQTT Client• webserver (secure HTTPs)• IO-Link Class A Master
Port Speed(s)	<ul style="list-style-type: none">• 10/100 Mbps• IO-Link COM1• IO-Link COM2• IO-Link COM3
IO-Link Version	IO-Link v1.1.3
Line Side Port(s)	(1) 7/8in - 16 UN2 thread nut 4-pin male axial
Load Side Port(s)	(1) 7/8in - 16 UN2 thread nut 4-pin female axial
External Power Requirement	24 VDC
Amperage Rating	9A
Load Current	2A/port
Indicator	LED
Housing Material	Die-cast zinc nickel-plated
IP Rating	IP67
Temperature Rating	-25 to 70 deg C
Includes	Marking tags
Programming Software	None, configure via Internet browser

Agency Approvals

UL Listed File #	E319845
UL Recognized File #	None
UL Hazardous File #	None
CE	View CE declarations
CSA File #	None
RoHS Status	Yes (See CE Doc)
EU REACH	View EU REACH document

Dimensional Drawings



2D Drawing PDF Link:
<https://cdn.automationdirect.com/static/drawings/2d/BNI00HM.pdf>
See store item page for other formats.