BX-DM1E-M-D Cut Sheet





BRX Do-more PLC, 12-24 VDC required, Ethernet and serial ports, microSD card slot, no on-board I/O.

For complete product information, please see this item on our store at the following link:



https://www.automationdirect.com/pn/BX-DM1E-M-D

Technical Specifications

- '	BBV B
Brand	BRX Do-more
Item	PLC
Total Memory	192k words
Ladder Memory	64k words
User Data Memory	128k words
Removable Media Type	MicroSD card slot
Programming Language	Ladder
Programming Software	Do-more Designer programming software v2.0 or later
Communication Port and Connection Type(s)	(1) Ethernet 10/100Base-T (RJ45) (1) RS-232/RS-485 (3-pin terminal)
Port Protocol(s)	Do-more protocol MQTT Client FTP Client Modbus RTU Master/Slave Modbus TCP TCP/IP EtherNet/IP explicit messaging scanner/adapter Ethernet remote I/O K-sequence Slave programming and monitoring
Port Speed(s)	• 10/100 Mbps • up to 115.2k baud

Real Time Clock/Calendar	Yes
Retentive Memory	Yes
Battery Backup	Yes
Maximum Expansion Modules Allowed	8
External Power Requirement	12-24 VDC
Maximum Number of PID Loops	100+ (configurable to memory limit)
Includes	BX-RTB03S and BX-RTB05 terminal blocks and D0-MC-BAT battery
Dangerous Goods	Battery Installed: Yes,Packaging Instructions: 970,UN Number: UN3091,Hazard Type: Lithium Batteries,Battery Type: Button,Lithium Content: 0.07,Replacement Battery: D0-MC-BAT,Generic Battery: CR2032

Agency Approvals

UL Listed File #	E185989
UL Recognized File #	None
UL Hazardous File #	None
CE	View CE declarations
CSA File #	None
RoHS Status	Yes (See CE Doc)
EU REACH	View EU REACH document