


CC600-18-5U-1 Cut Sheet



Quabbin control cable, unshielded, 5 conductors, 18 AWG, 16-stranded, tinned copper, PVC conductor insulation material, PVC jacket, gray, cut to length.

For complete product information, please see this item on our store at the following link:



<https://www.automationdirect.com/pn/CC600-18-5U-1>

Technical Specifications

Brand	Quabbin
Item	Cable
Wire/Cable Type	Control
UL Wire/Cable Type	AWM
Applicable Standards	UL 2586
Application	General purpose
Flexibility	Flexible
Voltage Rating	600V rated (UL)
Conductors	5 conductors
Conductor Size	18 AWG
Conductor Stranding	16-stranded
Conductor Material	Tinned copper
Conductor Insulation Material	PVC
Conductor Insulation Color	Black, brown, red, orange and yellow

Shielding	Unshielded
Jacket Material	PVC
Jacket Color	Gray
Nominal Overall Cable Diameter	0.275in
Bulk Length	Cut to length
Package Type	1 to 99ft = Coil, 100 to 515ft = 14 x 7in Reel, 516 to 735ft = 14 x 10in Reel, 736 to 1150ft = 16 x 10in Reel, 1151 to 1620ft = 18 x 10in Reel, 1621 to 2085ft = 18 x 13in Reel, 2086 to 4490ft = 24 x 17in Wooden Reel, 4491 to 7380ft = 30 x 17in Wooden Reel, 7381 to 10000ft = Large Wooden Reel

Agency Approvals

UL Listed File #	E69976
UL Recognized File #	None
UL Hazardous File #	None
CSA File #	LL51726
RoHS Status	Meets RoHS Chemical Restrictions - No CE (See RoHS Statement Below)
EU REACH	View EU REACH document
Other	RoHS Statement