## CFW320C14P0T4DB20 Cut Sheet





WEG Electric CFW320 series AC general purpose drive, enclosed, 460 VAC, 10hp with 3-phase input, SVC, V/Hz or VVW mode, C frame, integrated dynamic braking. Optional communication and I/O modules available.

For complete product information, please see this item on our store at the following link:



https://www.automationdirect.com/pn/CFW320C14P0T4DB20

## **Technical Specifications**

| •  |   |  |  |
|--|---|--|--|
| Brand  | WEG Electric                            | Number of Points per                             | 1  |
| ltem   | Drive                                   | Analog Input Common                              |  |
| Controller Type                                | General purpose                         | Input Resolution                                 | 10-bit   |
| Series   | CFW320                                  | Input Current Signal Range                       |  |
| Voltage Type                                   | AC                                      | Input Voltage Signal Range                       | 0-10 VDC   |
| Nominal Drive<br>Input Voltage                 | 460 VAC                                 | Number of Discrete<br>Input Points               | 4  |
| Nominal Drive<br>Output Voltage                | 460 VAC                                 | Nominal Discrete<br>Input Voltage                | 24 VDC   |
| Number of Input Phases                         | 3                                       | Discrete Input Type                              | Sinking/sourcing   |
| Number of Output Phases                        | 3                                       | Number of Non-Isolated<br>Discrete Input Commons | 1  |
| Horsepower By<br>Input Phase                   | 10hp with 3-phase input                 | Number of Points per<br>Discrete Input Common    | 4  |
| Amperage Rating                                | 14A                                     | Number of Discrete                               |  |
| Control Mode                                   | SVC, V/Hz or VVW                        | Output Points                                    | 1  |
| Safe Torque Off (STO)                          | No                                      | Nominal Discrete                                 | 250 VAC  |
| Temperature Rating                             | 0 to 50 deg C                           | Output Voltage                                   | 250 VAC  |
| Enclosure Type                                 | Enclosed                                | Discrete Output Type                             | Relay  |
| IP Rating                                      | IP20                                    | Relay Configuration                              | (1) Form C (SPDT) relay  |
| Mounting                                       | 35mm DIN rail, panel or wall            | Number of Isolated                               | 1  |
| Frame Size                                     | С                                       | Discrete Output Commons                          |  |
| Dynamic Braking                                | Integrated dynamic braking              | Number of Points per<br>Discrete Output Common   | 1  |
| Input Signal                                   | 4-20 mA, voltage or potentiometer input | •  | 0.54/2.5   |
| Output Type                                    | PWM output                              | Load Current                                     | 0.5A/point   |
| Reverse Capability                             | Built-in                                | Fuse Type  | User-supplied external fuse  |
| Internally Bypassed                            | No                                      | Programming Language                             | Ladder   |
| Carrier Frequency Range                        | 2.5-15 kHz                              | SCCR Rating                                      | 65kA SCCR  |
| Output Frequency Range                         | 0.1-400 Hz                              | Connector Type                                   | Screw terminals  |
| Number of Analog<br>Input Channels             | 1                                       | For Use With Additional Information              | 3-phase induction motors<br>Optional communication and I/O modules available |
| Number Of Input Channels                       | 1                                       |  | - F  |
| •  |   |  |  |
| Analog Input Signal Type                       | Current/voltage                         |  |  |
| Number of Non-Isolated<br>Analog Input Commons | 1                                       | _  |  |



## Agency Approvals

| UL Listed File #     | E184430                |  |  |
|----------------------|------------------------|--|--|
| UL Recognized File # | None                   |  |  |
| UL Hazardous File #  | None                   |  |  |
| CE                   | View CE declarations   |  |  |
| CSA File #           | None                   |  |  |
| RoHS Status          | Yes (See CE Doc)       |  |  |
| EU REACH             | View EU REACH document |  |  |

## **Dimensional Drawings**



2D Drawing PDF Link: https://cdn.automationdirect.com /static/drawings/2d/CFW320C14P0T4DB20.pdf See store item page for other formats.