

# DW-HD-613-M30-411 Cut Sheet



Contrinex inductive proximity sensor, tubular, 30mm diameter x 83mm body, 304 stainless steel housing, PNP, N.O., 15mm sensing distance, non-flush, 150 Hz switching frequency, IP67, pigtail.

For complete product information, please see this item on our store at the following link:



<https://www.automationdirect.com/pn/DW-HD-613-M30-411>

## Technical Specifications

<b>Brand</b>	Contrinex
<b>Item</b>	Proximity sensor
<b>Sensor Type</b>	Inductive
<b>Application</b>	High temperature
<b>Shape</b>	Tubular
<b>Housing Size</b>	30mm diameter x 83mm body
<b>Housing Material</b>	304 stainless steel
<b>Barrel Type</b>	Threaded
<b>Sensing Method</b>	Standard sensing
<b>Adjustable</b>	No
<b>Number of Wires</b>	3
<b>Switching Output</b>	PNP
<b>Operation Mode</b>	N.O.
<b>Sensing Distance</b>	15mm

<b>Mounting Type</b>	Non-flush
<b>IO-Link Compatible</b>	No
<b>Switching Frequency</b>	150 Hz
<b>Operating Voltage</b>	10-30 VDC
<b>Operating Temperature</b>	0 to 230C
<b>Weld Field Immune</b>	No
<b>Chip Immune</b>	No
<b>IP Rating</b>	IP67
<b>Connection</b>	Pigtail
<b>Conductor Size</b>	26 AWG
<b>Cable Length</b>	16.4ft/5m
<b>Jacket Material</b>	PTFE/PUR
<b>Additional Information</b>	Cable consists of 3m PTFE to amplifier and 2m PUR pigtail

## Agency Approvals

<b>UL Listed File #</b>	None
<b>UL Recognized File #</b>	None
<b>UL Hazardous File #</b>	None
<b>CE</b>	<a href="#">View CE declarations</a>
<b>CSA File #</b>	None
<b>RoHS Status</b>	Yes (See CE Doc)
<b>EU REACH</b>	<a href="#">View EU REACH document</a>

## Dimensional Drawings



2D Drawing PDF Link:  
<https://cdn.automationdirect.com/static/drawings/2d/DW-HD-613-M30-411.pdf>  
See store item page for other formats.