FF08D24UN Cut Sheet





Fandis Virdis series intake fan, side mount, 9.4 CFM, 24 VDC operating voltage, G3 (coarse) filter mat, NEMA 12, indoor use only, 3.62×3.62 in enclosure cutout, RAL 7035 light gray.

For complete product information, please see this item on our store at the following link:



https://www.automationdirect.com/pn/FF08D24UN

Technical Specifications

| Brand | Fandis |
|----------------------------------|------------------------|
| Series | Virdis series |
| Airflow Direction | Intake |
| Item | Fan |
| Mounting | Side |
| With Air Flaps | No |
| Filter Media | G3 (coarse) filter mat |
| Free Airflow | 9.4 CFM |
| Airflow with Grill and Filter(s) | 6.8 CFM |
| Operating Voltage | 24 VDC |
| Power Consumption | 2W |
| | |

| Current Draw | 85 mA |
|--------------------------------|------------------------------------|
| Electrical Connection | Screwless terminal block |
| Maximum Static Pressure | 28Pa |
| Operating Temperature | 14 to 131 deg F |
| Average Noise Level | 30 dBA |
| NEMA Rating | 12 |
| Application | Indoor use only |
| IP Rating | IP54 |
| Enclosure Cutout | 3.62 x 3.62in |
| Color | RAL 7035 light gray |
| Additional Information | Purchase exhaust grille separately |

Agency Approvals

| UL Listed File # | E500932 |
|----------------------|------------------------|
| UL Recognized File # | E237844 |
| UL Hazardous File # | None |
| CE | View CE declarations |
| CSA File # | 260922 |
| RoHS Status | Yes (See CE Doc) |
| EU REACH | View EU REACH document |

Dimensional Drawings



2D Drawing PDF Link: https://cdn.automationdirect.com/ /static/drawings/2d/FF08D24UN.pdf See store item page for other formats.