## IX7NHA010U-AD Cut Sheet





LS Electric servo drive, 1 kW, 230 VAC, 1 and 3-phase, (2) Ethernet 100Base-TX (RJ45) port(s), EtherCAT Slave and Modbus TCP. For use with 1 kW systems.

For complete product information, please see this item on our store at the following link:



https://www.automationdirect.com/pn/IX7NHA010U-AD

### **Technical Specifications**

Brand	LS Electric
Item	Servo drive
Voltage Type	AC
Amperage Rating	6.7A
Power Rating	1 kW
	230 VAC
Nominal Input Voltage	
Number of Input Phases	1 and 3
Output Type	SVPWM output
Steps per Revolution	Up to 19-bit (524288 ppr)
Encoder Output	Yes
Encoder Resolution	19-bit (524288 ppr)
Communication Port and Connection Type(s)	(2) Ethernet 100Base-TX (RJ45)
Port Protocol(s)	EtherCAT Slave Modbus TCP Server webserver (non-secure HTTP)
Port Speed(s)	100 Mbps
Temperature Rating	0 to 50 deg C
Enclosure Type	Enclosed
IP Rating	IP20
Mounting	Panel
Control Mode	Torque, velocity and position
Number of Discrete Input Points	6
Discrete Input Type	Sinking/sourcing
Number of Discrete Output Points	3
Discrete Output Type	Sinking
Number of Analog Input Channels	1
Analog Input Signal Type	Voltage
Input Voltage Signal Range	Input voltage signal range(s) of +/- 10 VDC
Number of Analog Output Channels	2
<b>Analog Output Signal Type</b>	Voltage

Output Voltage Signal Range	+/- 10 VDC
Tuning Mode	On-line auto/off-line auto/manual
Protection Type(s)	overcurrent overload over-temperature overvoltage undervoltage encoder error position error current sensing error
Configuration	Software
For Use With	1 kW systems
Derating	For 1-phase supply: This drive can only supply 200% max motor torque. Use iX7NHA020U-AD to get the standard 300%

# IX7NHA010U-AD Cut Sheet



### Agency Approvals

UL Listed File #	E479434
UL Recognized File #	None
UL Hazardous File #	None
CE	View CE declarations
CSA File #	None
RoHS Status	Yes (See CE Doc)
EU REACH	View EU REACH document

### **Dimensional Drawings**



2D Drawing PDF Link: https://cdn.automationdirect.com/ /static/drawings/2d/IX7NHA010U-AD.pdf See store item page for other formats.