MTR2-P50-3BD18 Cut Sheet





IronHorse MTR standard efficiency AC induction motor, general purpose and inverter rated, 1/2hp, 3-phase, 230/460 VAC, 1800rpm, TEFC, NEMA 56C frame, rolled steel, C-face/removable rigid base mount.

For complete product information, please see this item on our store at the following link:



https://www.automationdirect.com/pn/MTR2-P50-3BD18

Technical Specifications

IronHorse
Motor
MTR
Standard efficiency
70
AC
Induction
General purpose and inverter rated
1/2hp
3
230/460 VAC
1800rpm
1725rpm
None
TEFC
Round with square key

Shaft Diameter	5/8in
Shaft Material	1045 hot rolled (C-204) steel
Motor Frame	NEMA 56C
Frame Material	Rolled steel
Electrically Reversible	Yes
Insulation Class	Class F
IP Rating	IP43
Constant Torque Rating	4:1
Variable Torque Rating	10:1
Service Factor	1.15
Integrated Brake	No
NEMA Design	Design B
Junction Box Orientation	F1
Mounting	C-face/removable rigid base
Mounting Orientation	Horizontal or vertical

Agency Approvals

UL Listed File #	None
UL Recognized File #	None
UL Hazardous File #	None
CE	View CE declarations
CSA File #	256950
RoHS Status	Yes (See CE Doc)
EU REACH	View EU REACH document

Dimensional Drawings



2D Drawing PDF Link: https://cdn.automationdirect.com/ /static/drawings/MTR2-P50-3BD18.pdf See store item page for other formats.