## MTR2-P50-3BD36 Cut Sheet





IronHorse MTR standard efficiency AC induction motor, general purpose and inverter rated, 1/2hp, 3-phase, 230/460 VAC, 3600rpm, TEFC, NEMA 56C frame, rolled steel, C-face/removable rigid base mount.

For complete product information, please see this item on our store at the following link:



https://www.automationdirect.com/pn/MTR2-P50-3BD36

## **Technical Specifications**

| Brand             | IronHorse                          |
|-------------------|------------------------------------|
| Item              | Motor                              |
| Series            | MTR                                |
| Efficiency Group  | Standard efficiency                |
| Efficiency        | 67.5                               |
| Voltage Type      | AC                                 |
| Motor Type        | Induction                          |
| Motor Application | General purpose and inverter rated |
| Horsepower Rating | 1/2hp                              |
| Number of Phases  | 3                                  |
| Voltage Rating    | 230/460 VAC                        |
| Synchronous Speed | 3600rpm                            |
| Nameplate RPM     | 3450rpm                            |
| Overload Type     | None                               |
| Enclosure Type    | TEFC                               |
| Shaft Type        | Round with square key              |
|                   |                                    |

| Shaft Diameter           | 5/8in                         |
|--------------------------|-------------------------------|
| Shaft Material           | 1045 hot rolled (C-204) steel |
| Motor Frame              | NEMA 56C                      |
| Frame Material           | Rolled steel                  |
| Electrically Reversible  | Yes                           |
| Insulation Class         | Class F                       |
| IP Rating                | IP43                          |
| Constant Torque Rating   | 4:1                           |
| Variable Torque Rating   | 10:1                          |
| Service Factor           | 1.15                          |
| Integrated Brake         | No                            |
| NEMA Design              | Design B                      |
| Junction Box Orientation | F1                            |
| Mounting                 | C-face/removable rigid base   |
| Mounting Orientation     | Horizontal or vertical        |

## Agency Approvals

| UL Listed File #     | None                   |
|----------------------|------------------------|
| UL Recognized File # | None                   |
| UL Hazardous File #  | None                   |
| CE                   | View CE declarations   |
| CSA File #           | 256950                 |
| RoHS Status          | Yes (See CE Doc)       |
| EU REACH             | View EU REACH document |

## Dimensional Drawings



2D Drawing PDF Link: https://cdn.automationdirect.com/ /static/drawings/MTR2-P50-3BD36.pdf See store item page for other formats.