NA-419-1 Cut Sheet





Penn-Union neutral bar, tin-plated aluminum, 8 openings, 6 circuits, mounting hole position 1 and 8, copper or aluminum, AL9CU.

For complete product information, please see this item on our store at the following link:



https://www.automationdirect.com/pn/NA-419-1

Technical Specifications

| Brand | Penn-Union |
|------------------------|--|
| Item | Neutral bar |
| Material | Tin-plated aluminum |
| Number Of Openings | 8 |
| Number Of Circuits | 6 |
| Mounting Hole Position | 1 and 8 |
| Conductor Size | 14-2/0 AWG stranded copper, 14-8 AWG solid copper, 8-2/0 AWG stranded aluminum and 12-8 AWG solid aluminum |

| Conductor Material | Copper or aluminum |
|--------------------|---|
| Tightening Torque | 14-10 AWG 35 in-lb copper or aluminum, 8-2/0 AWG 120 in-lb copper, 8 AWG 50 in-lb aluminum and 6-2/0 AWG 120 in-lb aluminum |
| Dual Rating | AL9CU |
| Application | Neutral and grounding |

Agency Approvals

| UL Listed File # | E73393 |
|----------------------|--|
| UL Recognized File # | E12822 |
| UL Hazardous File # | None |
| CSA File # | None |
| RoHS Status | Meets RoHS Chemical Restrictions - No CE (See RoHS Statement Below) |
| EU REACH | View EU REACH document |
| Other | RoHS Statement |

Dimensional Drawings



2D Drawing PDF Link: https://cdn.automationdirect.com /static/drawings/2d/NA-419-1.pdf See store item page for other formats.