
Q2936-1 Cut Sheet





Quabbin Datamax Cat6 Ethernet cable, shielded, 4 twisted pairs, 26 AWG, 7-stranded, tinned copper, polyethylene conductor insulation material, PVC jacket, blue, cut to length.

For complete product information, please see this item on our store at the following link:



https://www.automationdirect.com/pn/Q2936-1

Technical Specifications

I	
Brand	Quabbin
Item	Cable
Series	Datamax
Protocol	Ethernet
Wire/Cable Type	Cat6 Ethernet
UL Wire/Cable Type	CMR and CMG
Application	Data
Flexibility	Semi-flexible
Voltage Rating	300V
Conductors	4 twisted pairs
Conductor Size	26 AWG
Conductor Stranding	7-stranded
Conductor Material	Tinned copper
Conductor Insulation Material	Polyethylene

Conductor Insulation Color	Pair 1: blue, white/blue, Pair 2: orange, white/orange, Pair 3: green, white/ green and Pair 4: brown, white/brown
Shielding	Shielded
Jacket Material	PVC
Jacket Color	Blue
Nominal Overall Cable Diameter	0.235in
Bulk Length	Cut to length
Package Type	 20 to 99ft = Coil 100 to 705ft =14 x 7in Reel 706 to 1010ft =14 x 10in Reel 1011 to 1545ft = 16 x 10in Reel 1546 to 2160ft = 18 x 10in Reel 2161 to 2810ft = 18 x 13in Reel 2811 to 5000ft = 24 x 17in Wooden Reel

Agency Approvals

UL Listed File #	E118830
UL Recognized File #	None
UL Hazardous File #	None
CE	None
CSA File #	None
RoHS Status	Meets RoHS Chemical Restrictions - No CE (See RoHS Statement Below)
EU REACH	View EU REACH document
Other	RoHS Statement