Q7131-1 Cut Sheet

AUTOMATIONDIRECT.com
www.automationdirect.com



Quabbin control and signal cable, unshielded, 5 conductors, 22 AWG, 7-stranded, tinned copper, PVC conductor insulation material, PVC jacket, gray, cut to length.

For complete product information, please see this item on our store at the following link:

https://www.automationdirect.com/pn/Q7131-1

Technical Specifications

Brand	Quabbin
Item	Cable
Wire/Cable Type	Control and signal
UL Wire/Cable Type	CM and AWM
Applicable Standards	UL 2464
Application	General purpose
Flexibility	Semi-flexible
Voltage Rating	300V
Conductors	5 conductors
Conductor Size	22 AWG
Conductor Stranding	7-stranded
Conductor Material	Tinned copper
Conductor Insulation Material	PVC

Conductor Insulation Color	Black, white, red, green and brown
Shielding	Unshielded
Jacket Material	PVC
Jacket Color	Gray
Nominal Overall Cable Diameter	0.199in
Bulk Length	Cut to length
Package Type	• 1 to 99ft = Coil • 100 to 985ft =14 x 7in Reel • 986 to 1405ft =14 x 10in Reel • 1406 to 2155ft = 16 x 10in Reel • 2156 to 3015ft = 18 x 10in Reel • 3016 to 3920ft = 18 x 13in Reel • 3921 to 8770ft = 24 x 17in Wooden Reel • 8771 to MAX = 30 x 17in Wooden Reel

Agency Approvals

UL Listed File #	E118830, E69976
CSA File #	LL51726
RoHS Status	Meets RoHS Chemical Restrictions - No CE (See RoHS Statement Below)
EU REACH	View EU REACH document
Other	RoHS Statement