Q7155-1 Cut Sheet

AUTOMATIONDIRECT.com
www.automationdirect.com



Quabbin control and signal cable, unshielded, 10 conductors, 22 AWG, 7-stranded, tinned copper, PVC conductor insulation material, PVC jacket, gray, cut to length.

For complete product information, please see this item on our store at the following link:

https://www.automationdirect.com/pn/Q7155-1

Technical Specifications

Brand	Quabbin
Item	Cable
Wire/Cable Type	Control and signal
UL Wire/Cable Type	CM and AWM
Applicable Standards	UL 2464
Application	General purpose
Flexibility	Semi-flexible
Voltage Rating	300V
Conductors	10 conductors
Conductor Size	22 AWG
Conductor Stranding	7-stranded
Conductor Material	Tinned copper
Conductor Insulation Material	PVC
Conductor Insulation Color	Black, white, red, green, orange, brown, blue, yellow, purple and gray

Shielding	Unshielded
Jacket Material	PVC
Jacket Color	Gray
Nominal Overall Cable Diameter	0.249in
Bulk Length	Cut to length
Package Type	• 1 to 99ft = Coil • 100 to 630ft =14 x 7in Reel • 631 to 900ft =14 x 10in Reel • 901 to 1380ft = 16 x 10in Reel • 1381 to 1925ft = 18 x 10in Reel • 1926 to 2505ft = 18 x 13in Reel • 2506 to 5600ft = 24 x 17in Wooden Reel • 5601 to 8960ft = 30 x 17in Wooden Reel • 8961 to MAX = Large Wooden Reel

Agency Approvals

UL Listed File #	E118830, E69976
CSA File #	LL51726
RoHS Status	Meets RoHS Chemical Restrictions - No CE (See RoHS Statement Below)
EU REACH	View EU REACH document
Other	RoHS Statement