

Q7465-1 Cut Sheet



Quabbin control and signal cable, shielded, (1) shielded pair, (2) unshielded conductors, 22 AWG, 7-stranded, tinned copper, PVC conductor insulation material, PVC jacket, gray, cut to length.

For complete product information, please see this item on our store at the following link:



<https://www.automationdirect.com/pn/Q7465-1>

Technical Specifications

Brand	Quabbin	Conductor Insulation Color	Black, red, green and white
Item	Cable	Shielding	Shielded
Wire/Cable Type	Control and signal	Jacket Material	PVC
UL Wire/Cable Type	CM and CMG	Jacket Color	Gray
Application	General purpose	Nominal Overall Cable Diameter	0.168in
Flexibility	Semi-flexible	Bulk Length	Cut to length
Voltage Rating	300V	Package Type	<ul style="list-style-type: none">• 20 to 99ft = Coil• 100 to 1380ft = 14 x 7in Reel• 1381 to 1975ft = 14 x 10in Reel• 1976 to 3025ft = 16 x 10in Reel• 3026 to 4230ft = 18 x 10in Reel• 4231 to 5000ft = 18 x 13in Reel
Conductors	(1) shielded pair, (2) unshielded conductors		
Conductor Size	22 AWG		
Conductor Stranding	7-stranded		
Conductor Material	Tinned copper		
Conductor Insulation Material	PVC		

Agency Approvals

UL Listed File #	E118830
CSA File #	LL51726
RoHS Status	Meets RoHS Chemical Restrictions - No CE (See RoHS Statement Below)
EU REACH	View EU REACH document
Other	RoHS Statement